



THE NEXT-GENERATION

Eco-friendly materials

-Where Quality, Reliability and Support meets you



HANGZHOU HYDROTECH CO., LTD.

TEL: 0086-571-85192560 / 85192160

FAX: 0086-571-85195380

EMAIL: sales@haitianchina.com.cn

WEB: www.chinahdht.com





INNOVATIVE PRODUCT RESPONSIBLE PRODUCTION SUSTAINABLE BUSINESS CONDUCT





COMPANY PROFILE

Hangzhou Hydrotech Co., Ltd. was established in 2001. The company mainly focuses on manufacturing, R&D and sales of sublimation transfer paper, water-based printing ink for decorative paper and wrapping paper. In order to meet the speedy development requirement from domestic and foreign market, the company owns three wholly owned subsidiaries (Hydrotech Trading, Quzhou Dongda Composite Material Technology Co., Ltd. and Runyi Science & Technology), realizing the integration of industry chain and professionally operating different products.

The company owns a reasonable structured R&D group consisting of professors, senior engineers and engineers. The patents covers the whole product series with independent intellectual property rights.

The company has built a modern enterprise management team to ensure standardization, process-oriented and efficient operation, possessing obvious technical advantages and strong development power in the application of sublimation transfer paper, water-based ink for decorative paper and wrapping paper.

MILESTONE

PROMOTE QUALITY DEVELOPMENT *浙江、*学国家大学科技园

2001&2007

- Established in Zhejiang University National Science Park in 2001;
- Officially located in Tonglu Economic Zone and appraised as a science and technology enterprise in Zhejiang Province in 2007;
- It passed the ISO 9001:2000 certification of Swiss SGS Company.

2009

- Sublimation Transfer Paper had been put into production and the first high-speed production line had been built in China;
- Appraised as the National Key High-technology Enterprises.

2012&2015

- Built the second high-speed production line;
- Established Zhejiang Provincial R & D Center.

- 2018
- · Acquisition of Quzhou Dongda Special Paper Co., Ltd. as paper production base;
- Built a new pulp paper line;
- Built the third high-speed production line.

- 2020
- •The fourth high-speed production line of sublimation transfer paper was put into production:
- •Started the construction of a new plant.
- •Built the fifth high-speed

2022

transfer paper; •The new workshop of ink was

production lines of sublimation

put into production.



中华人民共和国国家标准 national standards of People's Republic of China

PATENTS

The company has obtained nearly 40 authorized patents, including more than 20 national invention patents, 13 industrialized patents, and more than 10 research achievements that are currently being applied for. New applications are for 8-10 patents per year, and patent technology is covering each product.

STANDARDS

Zhejiang manufacturing standards for sublimation transfer paper T/ZZB 1950-2020 QB/T 5477-2019 GB/T 38153.2-2019 GB/T 28995-2012 GB/T 13217.1-2020





TECHNOLOGY

ADVANCED GREEN SUSTAINABLE

PRODUCT

CREATE VALUE FOR CUSTOMERS





Super Speed

High Speed

Sticky

Industrial

Sheets

DTF3.0-HP

Grease-proof paper

Fluoride-free grease-proof paper

Waxed paper

Bakery paper

Kraft paper

5000 Series

3000 Series

Pearl Series

SUBLIMATION PAPER

FEATURES:

Fast drying speed, superb transfer rate, vivid color, high definition.

PAPER-BASED HEAT TRANSFER FILM-DTF

FEATURES:

The surface of pattern and clothing always keeps dry and clean, energy-saving, environmental protection, and completely recyclable.

WRAPPING PAPER

FEATURES:


Excellent printing performance, good stiffness and strength, no fluorescent substances, biodegradable.

WATER-BASED PRINTING INK FOR DECORATIVE PAPER

FEATURES:

High definition, strong texture, good light and heat resistance, good printing stability.









SERVICE

PROFESSIONAL TIMELY COMPREHENSIVE



CONSULTING

Check the production index;
Analyze the application process;
Analyze and validate the key problems;
Deeply understand the reasons of problems.



PROFESSIONAL DOCKING

Professional engineers diagnose by telephone, video and on the spot;
Confirm the key of products or problems;
Provide comprehensive implementation plan and follow-up evaluation measures;
Solve problems!



TIMELY SERVICE

After-sales service telephone: +8618858295088, timely reply within 8 hours;

After-sales service engineers arrive within 24 hours in the province, arrive within 72 hours outside the province.

SUPER SPEED SUBLIMATION PAPER







X8410 / 8409 / 8408 / 8407

Large ink capacity, fast drying speed, X8400 will give you completely different experience of instant ink drying.

FEATURE

Ultra fast printing speed and instant ink drying

Large ink absorption and good smoothness

Anti-curling in high temperature

Superb adaptability for various application environments

SPECIFICATION

| MODEL | WIDTH | LENGTH | JUMBO ROLL |
|-------|-------------------------------------------------------|----------------|------------|
| X8410 | 610mm (24inch) 914mm (36inch) | 30/50/100/200m | 7000m |
| X8409 | 1118mm (44inch) 1520mm (60inch) 1620mm (64inch) | 100/200m | 8000m |
| X8408 | 1520mm (60inch) 1620mm (64inch) | 150/200m | 8000m |
| X8407 | | 200m | 10000m |

^{*}Other widths, lengths and jumbo rolls can be customized according to your requirements.

PERFORMANCE

| MODEL | GRAM (g/m2) | DRYING RATE | TRANSFER RATE | INK CAPACITY |
|-------|----------------|-------------|---------------|------------------|
| X8410 | 100 | *** | **** | * * * * * |
| X8409 | 90 | **** | **** | * * * * * |
| X8408 | 80 | **** | **** | * * * * |
| X8407 | 58 | *** | **** | * * * * |

^{*}The more marks, the better.

Put in the printing environment at least 24 hours before usage.

RHT-6110 / 6108 / 6107 / 6105

Meet your triple requirements: high speed printing, fast drying; large ink absorbing capacity, suitable for dark transfer; rich color performance.

FEATURE

High ink amount printing

High speed printing and fast drying

Superb transfer rate, excellent color density

Outstanding detail printing

SPECIFICATION

| MODEL | WIDTH | LENGTH | JUMBO ROLL |
|----------|------------------------------------|----------|------------|
| RHT-6110 | 610mm(24inch) | 100/200m | 7000m |
| RHT-6108 | 914mm(36inch) 1118mm (44inch) | 100/200m | 8000m |
| RHT-6107 | 1500mm (59inch) 1520mm (60inch) | 200m | 11000m |
| RHT-6105 | 1620mm (64inch) | 200m | 15000m |

^{*}Other widths, lengths and jumbo rolls can be customized according to your requirements.

PERFORMANCE

| MODEL | GRAM (g/m2) | DRYING RATE | TRANSFER RATE | INK CAPACITY |
|----------|----------------|-----------------|---------------|----------------|
| RHT-6110 | 100 | *** | **** | ** |
| RHT-6108 | 80 | \$\$\$\$\$ | **** | |
| RHT-6107 | 61 | \$\$\$\$ | **** | * * * * |
| RHT-6105 | 48 | \$\$\$\$ | **** | 4 4 4 6 |

^{*}The more marks, the better.

Put in the printing environment at least 24 hours before usage.



^{*}Suggested printing conditions: 25℃, 50%RH.

^{*}Suggested printing conditions: 25°C, 50%RH.

STICKY SUBLIMATION PAPER







Specifically designed for applications in stretch fabrics by thermally stick on it, thus effectively avoid shrinkage of fabrics and offering extraordinary performance in detail printing.

FEATURE

Thermally stick to various kinds of stretchy fabrics, stickiness stability

Avoiding shrinkage of fabrics and suitable for all different weather

conditionsFast drying speed

Superb transfer rate, extraordinary detailed printing

SPECIFICATION

| MODEL | WIDTH | LENGTH | JUMBO ROLL |
|----------|-------------------------------------------------------------------------|----------|------------|
| RHT-6510 | 914mm (36inch) 1118mm (44inch) 1520mm (60inch) 1620mm (64inch) | 100/200m | 7000m |

^{*}Other widths, lengths and jumbo rolls can be customized according to your requirements.

PERFORMANCE

| MODEL | GRAM (g/m2) | DRYING RATE | TRANSFER RATE | INK CAPACITY |
|----------|----------------|-------------------|---------------|--------------|
| RHT-6510 | 100 | \$\$\$\$\$ | **** | **** |

^{*}The more marks, the better.

Put in the printing environment at least 24 hours before usage.

INDUSTRIAL SUBLIMATION PAPER





Cost-effective products, satisfactory overall performance. Fast drying speed, especially suitable for high-speed printing.

FEATURE

Anti-curling

Large ink absorbing capacity and wide printing adaptability

Decolorization is faster and production efficiency is improved

Superb transfer rate, vivid image

SPECIFICATION

| MODEL | WIDTH | MINI ROLL | JUMBO ROLL |
|----------|------------------------------------|------------|------------|
| RHT-7106 | 1520mm (60inch) 1620mm (64inch) | 1000/2000m | 12000m |
| RHT-7104 | | 1000/2000m | 15000m |
| RHT-7103 | | 1000/2000m | 16000m |

^{*}Other widths, lengths and jumbo rolls can be customized according to your requirements.

PERFORMANCE

| MODEL | GRAM (g/m2) | DRYING RATE | TRANSFER RATE | INK CAPACITY |
|----------|----------------|-------------|---------------|----------------|
| RHT-7106 | 51 | 5555 | **** | * * * * |
| RHT-7104 | 43 | 5555 | **** | * * * * |
| RHT-7103 | 35 | 5555 | **** | * * * |

^{*}The more marks, the better.

Put in the printing environment at least 24 hours before usage.



^{*}Suggested printing conditions: 25°C, 50%RH.

^{*}Suggested printing conditions: 25°C, 50%RH.

SHEETS SUBLIMATION PAPER





The sublimation transfer paper of Hangzhou Hydrotech Co., Ltd. has the advantages of high transfer rate, fast drying speed, bright color and stable quality. It is widely used in fashion, home textiles, sports, advertising signs, hard plates and other fields.

SPECIFICATION

| MODEL | GRAM (g/m²) | SIZE (inch) | SHEETS PER PACK | PACK PER CARTON | CARTON PER PALLET |
|-------|----------------|-------------|--------------------|--------------------|----------------------|
| | | 8.3"×11.7" | 100 | 20 | 80 |
| S8412 | 125 | 16.5"×11.7" | 50/100 | 20/10 | 80 |
| | | 13"×19" | 50 | 25 | 60 |
| | 100 | 8.3"×11.7" | 100 | 20 | 80 |
| | | 16.5"×11.7" | 50/100 | 20/10 | 80 |
| S8410 | | 8.5"×11" | 100 | 20 | 80 |
| | | 11"×17" | 100 | 10 | 80 |
| | | 13"×19" | 50 | 25 | 60 |

■ BEST TRANSFER CONDITION

| SUBSTRATES | TEMPERATURE | TIME |
|-----------------|-------------|---------|
| Polyester fiber | 375F-190C | 20 sec |
| Aluminum plate | 340F-170C | 40 sec |
| Ceramics | 355F-180C | 200 sec |
| Glass | 375F-190C | 100 sec |
| Stone Board | 340F-170C | 300 sec |
| Mousepad | 390F-200C | 30 sec |

PRODUCT CATALOG

| TYPE | MODEL | GRAM (g/m²) | MINI ROLL | JUMBO ROLL |
|-------------|----------|-------------|-----------|------------|
| | X8410 | 100 | 0 | 0 |
| Super Speed | X8409 | 90 | • | • |
| Super speed | X8408 | 80 | 0 | 0 |
| | X8407 | 58 | 0 | • |
| | RHT-6110 | 100 | 0 | 0 |
| High Spood | RHT-6108 | 80 | 0 | • |
| High Speed | RHT-6107 | 61 | 0 | 0 |
| | RHT-6105 | 48 | 0 | 0 |
| Sticky | RHT-6610 | 100 | 0 | 0 |
| | RHT-7106 | 51 | 0 | • |
| Industrial | RHT-7104 | 43 | 0 | 0 |
| | RHT-7103 | 35 | 0 | 0 |
| Shoots | S8412 | 125 | | |
| Sheets | S8410 | 100 | | |



