JEMA

箭 马 缝 纫 机

JEMA SEWING MACHINE

箭马中国切带机领先品牌之一

JEMA is a Top Brand of Cutting Machine in China

JEMA is a Top Brand of Cutting Machine in China



台州市箭马缝纫机有限公司
TAIZHOU JEMA SEWING MACHINE CO., LTD
地址：浙江省台州市椒江区下陈街道刘洋工业区
ADD: Liuyang Industrial Zoon, Xiachen Street, Jiaojiang District, Taizhou City, Zhejiang Province, China
Tel: 0086-576-88172026 / 88157528 / 88172528
Fax: 0086-576-88172167
International Trade Department
Tel: 0086-576-88177528

2025版本目录产品外观、规格如有改动，恕不另行通知，请以实物为准！

2025 This product appearance, specifications are subject to change, without notice, refer to the actual product!

全国免费客服热线：
800-857-6835
www.chinajema.com
www.中国切带机.com
E-mail: jema@chinajema.com

了解切带机的三步曲
LEARN TRILOGY CUTTING MACHINE

切带机是什么机器？ Cutting machine, what's this machine?

切带机是集气、机电一体化的新型专机，它是用输入电脑程序自动控制机械、气缸的动作，利用刀片或声波来切断材料，是一款切断各种带状物品的专用设备。目前有机械式切带机、电脑切带机、超声波电脑切带机等。

Cutting machine is a air cylinder、mechanotronics mechanical-electrical integration new special machines, which is entered into a computer program to automatically control machinery、cylinder movement, through to using the blade or ultrasonic waves to cut off all kinds of ribbon items of special equipment. There are have mechanical cutting machine, automatic cutting machine, ultrasonic automatic cutting machine etc.

切带机是用在哪些领域？ Cutting machine, what fields is this machine used for?

该设备是用在：箱包的包带切断、鞋、帽上的带子、魔术贴、各种商标、塑料软管、各种拉链、各种软电线、电脑排线、胀缩管、松紧带等。

Cutting machine is used for: bag band cutting, shoes, hats tape, velcro, elastic bands, Soft plast tube, computer cables, all kinds of labels, zippers and fine wire.

切带机能给用户带来什么好处？ What advantage does this cutting machine give to users?

该设备能使用户提高产品质量、提高产品效益、据用户反馈：（使用该设备一台机器可以节省 2-3 个工人）。

Cutting machine enable users to promote products quality, improve produce efficiency, according to user feedback: (it can save 2-3workers when we use this equipment)

产品型号认知：
Model Differentiation:

JM-120HLR

品牌名称 Brand | 系列编码 Products Series | 功能编码 Products Functions

系列编码 Products Series	切带机类别 Type of Cutting Machine
2200	超声波电脑切带机 Ultrasonic Cutting Machine
150	多功能电脑切带机 Automatic Multi-function Cutting Machine
130	电脑切带机 Heavy-duty Auto-cutting Machine
120	电脑切带机 Automatic Cutting Machine
110	简易电脑切带机 Economical Auto-cutting Machine
817	机械式切带机 Mechanical Cutting Machine

功能编码 Products Functions	功能区分 Functional Explanation
L	冷刀 Cold Knife Cutter
LR	冷、热刀 Cold & Hot Knife Cutter
H	热刀 Hot Knife Cutter
SH	热刀红外 Auto-label Hot Knife Cutter
HLR	冷、热刀红外 Auto-label Cold & Hot Knife Cutter
HL	冷刀红外 Auto-label Cold Knife Cutter
HX	热刀斜角、直角 Bevel & Straight Cutter
R	专门切魔术贴 Velcro Tape Round Shape Cutter



LR
在不加热的情况下是冷刀，可以切 L 上的所有材料。加热后可以切尼龙材质，切边热封不散丝。但对厚料、棉质材质效果不佳。

If closing the heating switch, the machine will become a cold cutter and it can cut a variety materials same as "L" . It can cut nylon materials with sealing the edge once open the heat switch except the thick and cotton materials.

L
可以切不同材质如：尼龙、棉、塑料软管、电脑排线、胀缩管等材料，但对尼龙材质切口会散丝。

It can cut a variety of different materials such as: nylon tape, cotton tape, soft plastic tube, computer cables etc, but only cold cutting without heat-sealing function.

H
可以切尼龙、松紧带、魔术贴等尼龙材质，对一般厚度材质可以热封，切边不散丝。但不能切棉质材料。

It can cutting variety of different materials same as "L" . In addition to these,especially to sealing function is good at melting normally thick materials except cotton materials.

SH
在 H 所有的功能上，通过加装红外传感器，可以切各种商标。

This same as "H" function,it has color sensor device so it also can cutting varity of different label materials.

HLR
在 LR 的所有功能上，通过加装红外传感器，可以切各种商标。

This same as "LR" function,it has color sensor device so it also can cutting varity of different label materials.

HL
在 L 的所有功能上，通过加装红外传感器，可以切各种商标。

This same as "L" function,it has color sensor device so it also can cutting varity of different label materials.

HX
斜角切出的产品是斜面的，直角切出来的产品直面的，通过刀架平台上的螺丝可以转换斜角或直角。

It is a bevel & straight cutting machine with hot knife to sealing the edge,do not change the knife and direct loosen the screw to change the knife angle to reached customers request.

R
通过客人要求宽度和形状定做刀模。

It is a velcro cutting machine,it can cutting many different shapes to reached customers request!



JM-2100
超声波电脑切带机（直角）
Ultrasonic Cutting Machine (Right Angle)





功能特性
高速：每分钟可切断150 片（以50mm 长度为例）。
高精度：采用高精度步进电机驱动，以保证每次操作的高精确性。
切断面平整：采用进口大功率高效换能器，轻松切断各种不同厚、薄材料，切断面平整、无毛刺、不散丝。
自动操作：只需设定您所需的如：切断长度、数量等参数。其余工作电脑自动完成。
故障自检：切刀座、无材料一旦出现故障，系统将自动在屏幕上显示错误代码。
自动暂停：一旦材料用完，系统将自动停止工作。
记忆功能：在开关关闭前，自动储存当前所设置的所有参数。

可切断材质
各种编织带、魔术贴、鞋带、拉链、商标、各种皮质带料等。

Special features:
High speed: It can cut 150 pcs per minute.(e.p. 50 mm long)
Accuracy: Adopt high-accuracy stepping motor drive.
Cutting Type: Imported high-power efficient transducer, easy to cut off variety of thick, thin materials, cutting surface smoothly without burr, it is not frayed.
Automatic operation: It works automatically only by setting length , quantity.
Computerised: Automatic work,stop.The special fault by self-diagnosis. direct show the fault problem on the screen, it will easy for you to find clear way to repair.
Automatic stopper: It stops automatically if materials run out during operation.
Memory: Set-length, set quantity & set speed are not erased even if power off&on.

Applications:
All kinds of woven belt, velcro, shoelace, zipper, safe belt, leather strap etc.

型号 Model	切断长度 (mm) Cutting Length	50mm切断速度 (p/min) Cutting Speed	最大切断宽度 (mm) Max. Cutting Width	声波频率 (Hz) Sound Frequency	建议气压 (Mpa) Recommended Pressure	电压 (v) Voltage	功率 (kw) Power	声波功率 (kw) Power	重量 (kg) Weight	机箱包装尺寸 L.W.H(mm) Stand Package Size
JM-2100	50-99999	150	150	15K	0.4-0.7	110/220	3	2.6	150	860x600x1530



JM-2200
超声波电脑切带机（直角/转角）
Ultrasonic Cutting Machine (Right Angle/Bevel)





功能特性
高速：每分钟可切断 150 片(以 50mm 长度为例)。
高精度：采用高精度步进电机驱动，以保证每次操作的高精确性。
切刀平台共享：在同一切刀平台上，可以更换不同的刀模，如：直角、圆角、燕尾等形状。
转角功能：只要输入长度、宽度、角度等参数，电脑将自动切出你所需的如：菱形、平行四边形、方形、宝塔形等形状。
切断面平整：采用进口大功率高效换能器，轻松切断各种不同厚、薄材料，切断面平整、无毛刺、不散丝。
自动操作：只需设定您所需的如：切断长度、数量、角度等参数。其余工作电脑自动完成。
故障自检：切刀座、无材料一旦出现故障，系统将自动在屏幕上显示。
自动暂停：一旦材料用完，系统将自动停止工作。
记忆功能：在开关关闭前，自动储存当前所设置的所有参数。

可切断材质
各种编织带、魔术贴、鞋带、拉链、商标、各种皮质带料等。

Special features:
High speed: It can cut 150 pcs per minute.(e.p. 50 mm long)
Accuracy: Adopt high-accuracy stepping motor drive.
Share Platform: The special technique of sharing platform can carry varity shapes of knife moulds and replace mould quickly. E.p. Straight knife, round knife, swallow tail and punching mould shape etc.
Multi-Angle: By use of multi-angle cut fuction of straight knife, can cut many shapes as parallelogram, rhombic, trapeaoid etc.
Cutting Type: Imported high-power efficient transducer, easy to cut off variety of thick, thin materials, cutting surface smoothly without burr, it is not frayed.
Automatic Operation: It works automatically only by setting length , quantity.
Computerised: Automatic work,stop.The special fault by self-diagnosis.direct show the fault problem on the screen, it will easy for you to find clear way to repair.
Automatic stopper: It stops automatically if materials run out during operation.
Memory: Set-length, set quantity & set speed are not erased even if power off&on.

Applications:
All kinds of woven belt, velcro, shoelace, zipper, safe belt, leather strap etc.

型号 Model	切断长度 (mm) Cutting Length	50mm切断速度 (p/min) Cutting Speed	最大切断宽度 直角/转角(mm) Max. Cutting Width	声波频率 (Hz) Sound Frequency	建议气压 (Mpa) Recommended Pressure	电压 (v) Voltage	功率 (kw) Power	声波功率 (kw) Power	重量 (kg) Weight	机箱包装尺寸 L.W.H(mm) Stand Package Size
JM-2200	50-99999	150	100/35	15K	0.4-0.7	110/220	3	2.6	150	860x600x1530



JM-150HX
多功能电脑切带机（转角）
Auto-cutting Machine (Multi-function, Bevel Cutter)





功能特性
高速：每分钟可切断 150 片(以 50mm 长度为例)。
高精度：采用高精度步进电机驱动，以保证每次操作的高精确性。
转角功能：只要输入长度、宽度、角度等参数，电脑将自动切出你所需的如：菱形、平行四边形、方形、宝塔形等各种形状。
冲孔装置：根据用户需要，可冲不同大小直径的孔。
切断面平整：刀刃采用优质钢材制成。热刀可对彩色丝带、轻薄编织带的切断面进行高温热封，且封口平整无毛刺、不散丝。
自动操作：只需设定您所需的如：切断长度、数量、角度等参数。其余工作电脑自动完成。
故障自检：切刀座、无材料、色标传感器、转刀座一旦出现故障，系统将自动在屏幕上显示错误代码。
自动暂停：一旦材料用完，系统将自动停止工作。
记忆功能：在开关关闭前，自动储存当前所设置的所有参数。

可切断材质
各种编织带、魔术贴、鞋带、商标等各种尼龙材质。

Special features:
High speed: It can cut 150 pcs per minute.(e.p. 50 mm long)
Accuracy: Adopt high-accuracy stepping motor drive.
Multi-Angle: By use of multi-angle cut fuction of straight knife,it can cut many shapes as parallelogram,rhombic,trapeaoid ,etc by only set the length,quantity,angle.
Punching Device: According to the needs of user,it can punch different size of the diameter of the holes.
Cutting Type: The blade is made of high quality steel.Hot cutter can cut ribbon,thin woven belt and the hot knife melts the end of the tape,cutting is sealed neatly, smoothly without fraying.
Automatic operation: It works automatically only by setting length , quantity and angle.
Computerised: Automatic work,stop.The special fault by self-diagnosis.direct show the fault problem on the screen,it will easy for you to find clear way to repair.
Automatic stopper: It stops automatically if materials run out during operation.
Memory: Set-length,set quantity&set speed are not erased even if power off&on.

Applications:
All kinds of woven belt,velcro,shoelace,plastic soft tube,computer cable,label etc.

型　号 Model	切断长度 (mm) Cutting Length	最大切断宽度 直角/转角 (mm) Max. Cutting Width	最大收料高度 (mm) Max. Receipts Height	50mm切断速度 (p/min) Cutting Speed	刀片最高温度 (℃) Max. Blade Temp	建议气压 (Mpa) Recommended Pressure	电压 (v) Voltage	冲孔直径 (mm) Punching Diameter	功率 (Kw) Power	重量 (kg) Weight	包装尺寸 L.W.H (mm) Package Size
JM-150HX	30-99999	65/40	-	150	420	0.2~0.6	110/220	2-8	1.05	77.5	820x570x780

JM-150H

多功能电脑切带机（热刀）

Auto-cutting Machine (Multi-function, Hot Cutter)



JM-300S 送带机选配
Tape Feeder Optional





功能特性

高速：每分钟可切断 150 片(以 50mm 长度为例、带收料装置)。
高精度：采用高精度步进电机驱动,以保证每次操作的高精确性。
收料功能： 根据设定收料数量,机器自动叠料,方便用户捆扎。
冲孔装置： 根据用户需要,可冲不同大小直径的孔。
切断面平整：刀刃采用优质钢材制成。热刀可对彩色丝带、轻薄编织带的切断面进行高温热封厚、且封口平整无毛刺、不散丝。
自动操作：只需设定您所需的如：切断长度、数量等参数。其余工作电脑自动完成。
故障自检：切刀座、无材料、色标传感器、转刀座一旦出现故障，系统将自动在屏幕上显示。
自动暂停：一旦材料用完，系统将自动停止工作。
记忆功能：在开关关闭前，自动储存当前所设置的所有参数。

可切断材质

各种编织带、魔术贴、鞋带、商标等各种尼龙材质。

Special features:

High speed: It can cut 150 pcs per minute.(e.p. 50 mm long,it include collecting device)
Accuracy: Cut-length is accurate owing to a stepping motor.
Collecting Function: Setting the quantity, it will be collecting automatically, so that clients can be easily packed.
Punching Device: According to the needs of user,it can punch different size of the diameter of the holes.
Cutting Type: The blade is made of high quality steel.Hot cutter can cut ribbon,thin woven belt and the hot knife melts the end of the tape,cutting is sealed neatly, smoothly without fraying.
Automatic operation: It works automatically only by setting length and quantity. It stops automatically if materials run out during operation.
Computerised: Automatic work,stop.The special fault by self-diagnosis.direct show the fault problem on the screen,it will easy for you to find clear way to repair.
Memory: Set-length,set quantity&set speed are not erased even if power off&on.

Applications:

All kinds of woven belt,velcro,shoelace,plastic soft tube,computer cable,label etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	最大收料高度(mm)	50mm切断速度 (p/min)	刀片最高温度 (℃)	建议气压 (Mpa)	电压 (v)	冲孔直径 (mm)	功率 (Kw)	重　量 (kg)	包装尺寸L.W.H (mm)
Model	Cutting Length	Max. Cutting Width	Max. Receipts Height	Cutting Speed	Max. Blade Temp	Recommended Pressure	Voltage	Punching Diameter	Power	Weight	Package Size
JM-150H	30-99999	95	30	150	420	0.2-0.6	110/220	2-8	1.2	77.5	820x570x780

JM-150LR

多功能电脑切带机（冷、热）

Auto-cutting Machine (Multi-function, Cold & Hot Cutter)







功能特性

高速：每分钟可切断 150 片(以 50mm 长度为例,带收料装置)。
高精度：采用高精度步进电机驱动，以保证每次操作的高精确性。
收料功能：根据设定收料数量,机器自动叠料,方便用户捆扎。
冲孔装置：根据用户需要,可冲不同大小直径的孔。
切断面平整：刀刃采用优质钢材制成。热刀可对彩色丝带、轻薄编织带的切断面进行高温热封厚,且封口平整无毛刺、不散丝，但对厚料效果不佳。
自动操作：只需设定您所需的如：切断长度、数量等参数，其余工作电脑自动完成。
故障自检：切刀座、无材料、转刀座一旦出现故障，系统将自动在屏幕上显示。
自动暂停：一旦材料用完，系统将自动停止工作。
记忆功能：在开关关闭前，自动储存当前所设置的所有参数。

可切断材质

各种编织带、魔术贴、鞋带、商标等各种尼龙材质。

Special features:

High speed: It can cut 150 pcs per minute.(e.p. 50mm long,it include collecting device)
Accuracy: Cut-length is accurate owing to a stepping motor.
Collecting Function:Setting the quantity,it will be collecting automatically ,so that clients can be easily packed.
Punching Device: According to the needs of user,it can punch different size of the diameter of the holes.
Cutting type: The knife is made of high quality steel.Hot cutter can cut ribbon,thin woven belt and the hot knife melts the end of the tape,cutting is sealed neatly, smoothly without fraying, but except the thick materials.
Automatic operation: It works automatically only by setting length and quantity.
Computerised: Automatic work,stop.The special fault by self-diagnosis.direct show the fault problem on the screen,it will easy for you to find clear way to repair.
Automatic stopper: It stops automatically if materials run out during operation.
Memory: Set-length,set quantity&set speed are not erased even if power off&on.

Applications:

All kinds of woven belt,velcro,shoelace,plastic soft tube,computer cable,label etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	最大收料高度 (mm)	50mm切断速度 (p/min)	刀片最高温度 (℃)	建议气压 (Mpa)	电压 (v)	冲孔直径 (mm)	功率 (Kw)	重　量 (kg)	包装尺寸L.W.H (mm)
Model	Cutting Length	Max. Cutting Width	Max. Receipts Height	Cutting Speed	Max. Blade Temp	Recommended Pressure	Voltage	Punching Diameter	Power	Weight	Package Size
JM-150LR	30-99999	95	40	150	350	0.2-0.6	110/220	2-8	1.2	77.5	820x570x780

JM-150L

多功能电脑切带机（冷刀）

Auto-cutting Machine (Multi-function, Cold Cutter)



JM-300S 送带机选配
Tape Feeder Optional





功能特性

高速：每分钟可切断 150 片(以 50mm 长度为例,带收料装置)。
高精度：采用高精度步进电机驱动,以保证每次操作的高精确性。
收料功能：根据设定收料数量,机器自动叠料,方便用户捆扎。
冲孔装置：根据用户需要,可冲不同大小直径的孔。
切断面平整：刀刃采用优质钢材制成,保证了切断面的平整性。
自动操作：只需设定您所需的如：切断长度、数量等参数，其余工作电脑自动完成。
故障自检：切刀座、无材料、转刀座一旦出现故障，系统将自动在屏幕上显示。
自动暂停：一旦材料用完，系统将自动停止工作。
记忆功能：在开关关闭前，自动储存当前所设置的所有参数。

可切断材质

各种编织带、魔术贴、鞋带、塑料软管、电脑排线、商标等各种尼龙材质。

Special features:

High speed: It can cut 150 pcs per minute.(e.p. 50 mm long,it include collecting device)
Accuracy: Cut-length is accurate owing to a stepping motor.
Collecting Function:Setting the quantity,it will be collecting automatically ,so that clients can be easily packed.
Punching Device: According to the needs of user,it can punch different size of the diameter of the holes.
Cutting type: The blade is made of special steel,to make the cutting surface neatly and not frayed.
Automatic operation: It works automatically only by setting length and quantity.
Computerised: Automatic work,stop.The special fault by self-diagnosis.direct show the fault problem on the screen,it will easy for you to find clear way to repair.
Automatic stopper: It stops automatically if materials run out during operation.
Memory: Set-length,set quantity&set speed are not erased even if power off&on.

Applications:

All kinds of woven belt,velcro,shoelace,plastic soft tube,computer cable,label etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	最大收料高度 (mm)	50mm切断速度 (p/min)	刀片最高温度 (℃)	建议气压 (Mpa)	电压 (v)	冲孔直径 (mm)	功率 (Kw)	重　量 (kg)	包装尺寸L.W.H (mm)
Model	Cutting Length	Max. Cutting Width	Max. Receipts Height	Cutting Speed	Max. Blade Temp	Recommended Pressure	Voltage	Punching Diameter	Power	Weight	Package Size
JM-150L	30-99999	95	40	150	-	0.2-0.6	110/220	2-8	0.3	77.5	820x570x780

JEMA®
箭马中国切带机领先品牌之一
JEMA is a Top Brand of Cutting Machine in China

JM-130LR

电脑切带机（冷、热刀）

Heavy-duty (Cold & Hot) Knife Cutter







功能特性

高速：每分钟可切断 150 片(以 50mm 长度为例)。
高精度：采用高精度步进电机驱动,以保证每次操作的高精确性。
切断面平整：热刀可对彩色丝带、轻薄编织带的切断面进行高温热封且封口平整无毛边，但对厚料效果不佳。刀刃由优质进口钢材制成,使用寿命长。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换，页面功能直观易操作,设定方便。
补偿功能：因材料不同,切出的效果与输入尺寸不符时,只需输入实际切出的尺寸数值,系统自动补偿误差值。
故障自检：切刀传感器出错,无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。
自动操作：只需设定您所需的如：切断长度、数量等参数 ， 其余工作电脑自动完成。自动暂停：一旦材料用完，系统将自动停止工作。
记忆功能：在开关关闭前,自动储存当前所设置的所有参数。

可切断材质

尼龙编织带、彩色缎带、背包带等尼龙材质。

Special features:

High speed: It can cut 150 pcs per minute.(e.p. 50 mm long)
Accuracy: Cut-length is accurate owing to a stepping motor.
Cutting Type: Melting & cutting by hot knife, woven label is cut neatly without fraying but not for heavy materials and installed with anti-static electricity device.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation： After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Automatic operation: It works automatically only by setting length and quantity.Automatic stopper: It stops automatically if materials run out during operation.
Memory: Set-length, set quantity & set speed are not erased even if power off&on.

Applications:

Woven tapes, strip tapes, bag band etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度 (p/min)	刀片最高温度 (℃)	电压 (v)	建议气压 (mpa)	额定功率 (kw)	包装尺寸L.W.H (mm)	重　量 (kg)	机箱包装尺寸L.W.H (mm)	重量 (kg)	装箱率 (台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Suggested Pressure	Power	Package Size	Weight	Stand Package Size	Weight	Loading Rate Pic
JM-130LR	20-99999	200	150	350	110/220	0.3-0.6	0.9	675x645x695	105	550x445x465	20	2
JM-130LR	20-99999	300	150	350	110/220	0.3-0.6	1.5	675x742x695	120	655x470x470	22	2

JM-130H

电脑切带机（热刀）

Heavy-duty (Hot) Knife Cutter







功能特性

高速：每分钟可切断 150 片(以 50mm 长度为例)。
高精度：采用高精度步进电机驱动,以保证每次操作的高精确性。
切断面平整：热刀可对彩色丝带、轻薄编织带的切断面进行高温热封且封口平整无毛边,刀刃由优质进口钢材制成,使用寿命长。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换，页面功能直观易操作,设定方便。
补偿功能：因材料不同,切出的效果与输入尺寸不符时,只需输入实际切出的尺寸数值,系统自动补偿误差值。
故障自检：切刀传感器出错,无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。
自动操作：只需设定您所需的如：切断长度、数量等参数 ， 其余工作电脑自动完成。自动暂停：一旦材料用完，系统将自动停止工作。
记忆功能：在开关关闭前,自动储存当前所设置的所有参数。

可切断材质

尼龙编织带、彩色缎带、背包带等尼龙材质。

Special features:

High speed: It can cut 150 pcs per minute.(e.p. 50 mm long)
Accuracy: Cut-length is accurate owing to a stepping motor.
Cutting Type: Melting & cutting by hot knife, woven label is cut neatly without fraying and installed with anti-static electricity device.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation： After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Automatic operation: It works automatically only by setting length and quantity.Automatic stopper: It stops automatically if materials run out during operation.
Memory: Set-length, set quantity & set speed are not erased even if power off&on.

Applications:

Woven tapes, strip tapes, bag band etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度 (p/min)	刀片最高温度 (℃)	电压 (v)	建议气压 (mpa)	额定功率 (kw)	包装尺寸L.W.H (mm)	重　量 (kg)	机箱包装尺寸L.W.H (mm)	重量 (kg)	装箱率 (台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Suggested Pressure	Power	Package Size	Weight	Stand Package Size	Weight	Loading Rate Pic
JM-130H	20-99999	200	150	400	110/220	0.3-0.6	0.9	675x645x695	112	550x445x465	20	2

JM-130L

电脑切带机（冷刀）

Heavy-duty Cold Knife Cutter







功能特性

高速：每分钟可切断 150 片(以 50mm 长度为例)。
高精度：采用高精度步进电机驱动,以保证每次操作的高精确性。
切断面平整：刀刃由优质进口钢材制成,保证了切断面的平整性。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换，页面功能直观易操作,设定方便。
补偿功能：因材料不同，切出的效果与输入尺寸不符时，只需输入实际切出的尺寸数值,系统自动补偿误差值。
故障自检：切刀传感器出错，无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。
自动操作：只需设定您所需的如：切断长度、数量等参数，其余工作电脑自动完成。自动暂停：一旦材料用完，系统将自动停止工作。
记忆功能：在开关关闭前,自动储存当前所设置的所有参数。

可切断材质

编织带、魔术贴、塑料软管、鞋带、塑料拉链、电脑排线等。

Special features:

High speed: It can cut 150 pcs per minute.(e.p. 50 mm long)
Accuracy: Cut-length is accurate owing to a stepping motor.
Cutting Type: Cutting is neat due to using a cold cutter which is durable because they are made of high-speed steel.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation： After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Automatic operation: It works automatically only by setting length and quantity.Automatic stopper: It stops automatically if materials run out during operation.
Memory: Set-length, set quantity & set speed are not erased even if power off&on.

Applications:

Belt loop, soft tube, string, plastic zipper, elastic band, small webbing etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度 (p/min)	刀片最高温度 (℃)	电压 (v)	建议气压 (mpa)	额定功率 (kw)	包装尺寸L.W.H (mm)	重　量 (kg)	机箱包装尺寸L.W.H (mm)	重量 (kg)	装箱率 (台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Suggested Pressure	Power	Package Size	Weight	Stand Package Size	Weight	Loading Rate Pic
JM-130L	20-99999	200	150	-	110/220	0.3-0.6	0.3	675x645x695	107	550x445x465	20	2
JM-130L	20-99999	300	150	-	110/220	0.3-0.6	0.3	675x742x695	123	655x470x470	22	2



JM-130R
电脑切带机（圆角）
Velcro Tape Round Shape Cutter





功能特性：
高速：每分钟可切断 120 片(以 50㎜ 长度为例)。
高精度：采用高精度步进电机驱动,以保证每次操作的高精确性。
切断面平整：刀刃由优质进口钢材制成,保证了切断面的平整性。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换，页面功能直观易操作,设定方便。
补偿功能：因材料不同，切出的效果与输入尺寸不符时，只需输入实际切出的尺寸数值,系统自动补偿误差值。
故障自检：切刀传感器出错,无材料供给,一旦出现故障,系统将自动在屏幕上显示出错代码。
自动操作：只需设定您所需的如：切断长度、数量等参数，其余工作电脑自动完成。自动暂停：一旦材料用完,系统将自动停止工作。
记忆功能：在开关关闭前,自动储存当前所设置的所有参数。

可切断材质：
魔术贴。

Special features:
High speed: It can cut 120 pcs per minute.(e.p. 50 mm long)
Accuracy: Cut-length is accurate owing to a stepping motor.
Cutting Type: Cutting is neat due to using a cold cutter which is durable because they are made of high-speed steel.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation：After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Automatic operation: It works automatically only by setting length and quantity.Automatic stopper: It stops automatically if materials run out during operation.
Memory: Set-length, set quantity & set speed are not erased even if power off&on.

Applications:
Velcro tapes.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度(p/min)	刀片最高温度 (℃)	电压 (v)	建议气压 (mpa)	额定功率 (kw)	包装尺寸L.W.H (mm)	重　量 (kg)	机箱包装尺寸L.W.H (mm)	重量 (kg)	装箱率 (台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Suggested Pressure	Power	Package Size	Weight	Stand Package Size	Weight	Loading Rate Pic
JM-130R	20-99999	20-100	120	-	110/220	0.4-0.7	0.3	675x645x695	107	550x445x465	20	2



JM-120LR
电脑切带机（冷、热）
Auto-belt Loop Cutter (Cold & Hot)





功能特性：
高速：每分钟可切断 170 片。(以 50㎜ 长度为例)
高精度：每一次切断都由传感器、软件监控,切刀快速且精确。
切断面平整：刀刃由优质进口钢材制成，使用寿命长。热刀可对彩色丝带、编织带的切断面进行热封,且封口平整无毛边。
切刀次数：可设置多次切断,以达到切断的效果。
切刀速度：对于厚料且不容易切断的材料，可调节切刀速度，以达到材料的切断效果。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换,页面功能直观易操作,设定方便。
补偿功能：因材料不同，切出的效果与输入尺寸不符时，只需输入实际切出的尺寸数值,系统自动补偿误差值。
故障自检：切刀传感器出错,无材料供给,一旦出现故障,系统将自动在屏幕上显示出错代码。
自动操作、自动暂停：只需设定您所需的切断长度和数量，其余工作都自动完成。一旦材料用完,机器将自动停止工作。

可切断材质：
编织带、尼龙织带、彩色缎带、背包带等尼龙材质。

Special features:
High speed: It can cut 170 pcs per minute. (50 mm long)
Accuracy: Faster and accurate cut by the sensor and software.
Cutting type: Melting & cutting by hot knife, woven label is cut neatly without fraying but not for heavy materials and installed with anti-static electricity device.
Cutting times:It can set quantity cutting times to achieve good quality cut.
Cutter speed:It can set the cutter speed for some thick and strong materials to achieve cutting effective.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation：After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Automatic operation、Automatic stopper: It works automatically only by setting speed length quantity and temperature.It stops automatically if materials run out during operation.

Applications:
Belt loop, bag band, shrink tube, string, elastic band, plastic zipper etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度(p/min)	刀片最高温度 (℃)	电压 (v)	频率 (Hz)	额定功率 (kw)	建议气压 (mpa)	包装尺寸L.W.H (mm)	重　量 (kg)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Suggested Pressure	Package Size	Weight
JM-120LR	10-99999	100	170	350	110/220	50/60	0.7	0.3-0.4	560x420x405	16/21



JM-120LR-G
电脑切带机（冷、热）
Auto-belt Loop Cutter (Cold & Hot)





功能特性：
高速：每分钟可切断 170 片。(以 50㎜ 长度为例)
高精度：每一次切断都由传感器、软件监控,切刀快速且精确。
切断面平整：刀刃由优质进口钢材制成，使用寿命长。热刀可对彩色丝带、编织带的切断面进行热封,且封口平整无毛边。
切刀次数：可设置多次切断,以达到切断的效果。
切刀速度：对于厚料且不容易切断的材料，可调节切刀速度，以达到材料的切断效果。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换,页面功能直观易操作,设定方便。
补偿功能：因材料不同，切出的效果与输入尺寸不符时，只需输入实际切出的尺寸数值,系统自动补偿误差值。
故障自检：切刀传感器出错,无材料供给,一旦出现故障,系统将自动在屏幕上显示出错代码。
自动操作、自动暂停：只需设定您所需的切断长度和数量，其余工作都自动完成。一旦材料用完,机器将自动停止工作。

可切断材质：
编织带、尼龙织带、彩色缎带、背包带等尼龙材质。

Special features:
High speed: It can cut 170 pcs per minute. (50 mm long)
Accuracy: Faster and accurate cut by the sensor and software.
Cutting type: Melting & cutting by hot knife, woven label is cut neatly without fraying but not for heavy materials and installed with anti-static electricity device.
Cutting times:It can set quantity cutting times to achieve good quality cut.
Cutter speed:It can set the cutter speed for some thick and strong materials to achieve cutting effective.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation：After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Automatic operation、Automatic stopper: It works automatically only by setting speed length quantity and temperature.It stops automatically if materials run out during operation.

Applications:
Belt loop, bag band, shrink tube, string, elastic band, plastic zipper etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度(p/min)	刀片最高温度 (℃)	电压 (v)	频率 (Hz)	额定功率 (kw)	建议气压 (mpa)	包装尺寸L.W.H (mm)	重　量 (kg)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Suggested Pressure	Package Size	Weight
JM-120LR-G	10-99999	145	170	350	110/220	50/60	0.9	0.3-0.4	620x570x490	18/30

JEMA®
箭马中国切带机领先品牌之一
JEMA is a Top Brand of Cutting Machine in China



JM-120L
电脑切带机（冷刀）
Cold Knife Cutter





功能特性：
高速：每分钟可切断 170 片。(以 50㎜ 长度为例)
高精度：每一次切断都由传感器、软件监控,切刀快速且精确。
切断面平整：刀刃由优质进口钢材制成,保证了切断面的平整性。
切刀次数：可设置多次切断,以达到切断的效果。
切刀速度：对于厚料且不容易切断的材料，可调节切刀速度，以达到材料的切断效果。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换,页面功能直观易操作,设定方便。
补偿功能：只需输入实际切出的尺寸数值,便可准确切出系统设置的长度。
故障自检：切刀传感器出错,无材料供给,一旦出现故障,系统将自动在屏幕上显示出错代码。
自动操作、自动暂停：只需设定您所需的切断长度和数量，其余工作都自动完成。一旦材料用完,机器将自动停止工作。

可切断材质：
编织带、魔术贴、塑料软管、鞋带、塑料拉链、电脑排线等

Special features:
High speed: It can cut 170 pcs per minute. (50 mm long)
Accuracy: Faster and accurate cut by the sensor and software.
Cutting type:Cutting is neat due to using a cold cutter which is durable because they are made of high-speed steel.
Cutting times:It can set quantity cutting times to achieve good quality cut.
Cutter speed:It can set the cutter speed for some thick and strong materials to achieve cutting effective.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate , setting is convenient.
Compensation：After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Automatic operation、Automatic stopper: It works automatically only by setting speed length quantity and temperature.It stops automatically if materials run out during operation.

Applications:
Belt loop, soft tube, string, plastic zipper, elastic band, small webbing etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度(p/min)	刀片最高温度 (℃)	电压 (v)	频率 (Hz)	额定功率 (kw)	建议气压 (mpa)	包装尺寸L.W.H (mm)	重　量 (kg)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Suggested Pressure	Package Size	Weight
JM-120L	10-99999	105	170	-	110/220	50/60	0.3	0.3-0.4	560x420x405	16/21



JM-120HX
电脑切带机（转角）
Auto-cutting Machine (Bevel cutter)





功能特性：
高速：每分钟可切断 150 片。(以 50㎜ 长度为例)
高精度：每一次切断都由传感器、软件监控,切刀快速且精确。
切断面平整：刀刃由优质进口钢材制成,保证了切断面的平整性。
切刀次数：可设置多次切断,以达到切断的效果。
切刀速度：对于厚料且不容易切断的材料，可调节切刀速度，以达到材料的切断效果。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换,页面功能直观易操作,设定方便。
转角功能：只要输入长度、宽度、角度等参数,电脑将自动切出你所需的如：菱形、平行四边形、方形、宝塔形等各种形状。
补偿功能：只需输入实际切出的尺寸数值,便可准确切出系统设置的长度。
故障自检：切刀传感器出错,无材料供给,一旦出现故障,系统将自动在屏幕上显示出错代码。
自动操作、自动暂停：只需设定您所需的切断长度和数量，其余工作都自动完成。一旦材料用完,机器将自动停止工作。

可切断材质：
尼龙商标,织带,彩色缎带,背包带等尼龙材质。

Special features:
High speed: It can cut 150 pcs per minute. (50 mm long)
Accuracy: Faster and accurate cut by the sensor and software.
Cutting type:Cutting bevel is adjusted by hand. And cutting is neat due to using a cold cutter which is durable.
Cutting times:It can set quantity cutting times to achieve good quality cut.
Cutter speed:It can set the cutter speed for some thick and strong materials to achieve cutting effective.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Multi-Angle: By use of multi-angle cut fuction of straight knife,it can cut many shapes as parallelogram, rhombic, trapeaoid ,etc by only set the length,quantity,angle.
Compensation:After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Automatic operation、Automatic stopper: It works automatically only by setting speed length quantity and temperature.It stops automatically if materials run out during operation.

Applications:
Belt loop, ribbon tape, bag band, small webbing etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度(p/min)	刀片最高温度 (℃)	电压 (v)	频率 (Hz)	额定功率 (kw)	建议气压 (mpa)	包装尺寸L.W.H (mm)	重　量 (kg)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Suggested Pressure	Package Size	Weight
JM-120HX	50-99999	60/98	150	400	110/220	50/60	1	0.3-0.4	620x540x520	34

300M送带机可选装
Optional Auto-Feeder



JM-120H-300M
电脑切带机（热刀）配送带机
Hot Knife Cutter With Auto-Feeder





功能特性：
高速：每分钟可切断 170 片。(以 50㎜ 长度为例)
高精度：每一次切断都由传感器、软件监控,切刀快速且精确。
切断面平整：热刀可对彩色丝带、轻薄编织带的切断面进行热封,且封口平整无毛边。刀刃由优质进口钢材制成,使用寿命长。
切刀次数：可设置多次切断,以达到切断的效果。
切刀速度：对于厚料且不容易切断的材料，可调节切刀速度，以达到材料的切断效果。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换,页面功能直观易操作,设定方便。
补偿功能：只需输入实际切出的尺寸数值,便可准确切出系统设置的长度。
故障自检：切刀传感器出错,无材料供给,一旦出现故障,系统将自动在屏幕上显示出错代码。
自动操作、自动暂停：只需设定您所需的切断长度和数量，其余工作都自动完成。一旦材料用完,机器将自动停止工作。

可切断材质：
尼龙编织带、彩色缎带、背包带等尼龙材质。

Special features:
High speed: It can cut 170 pcs per minute. (50 mm long)
Accuracy: Faster and accurate cut by the sensor and software.
Cutting type: Melting & cutting by hot knife, woven label is cut neatly without fraying and installed with anti-static electricity device.
Cutting times:It can set quantity cutting times to achieve good quality cut.
Cutter speed:It can set the cutter speed for some thick and strong materials to achieve cutting effective.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation：After actual length data inputted, accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Automatic operation、Automatic stopper: It works automatically only by setting speed length quantity and temperature.It stops automatically if materials run out during operation.

Applications:
Strip tapes, ribbon tape, bag band, small webbing etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度(p/min)	刀片最高温度 (℃)	电压 (v)	频率 (Hz)	额定功率 (kw)	建议气压 (mpa)	包装尺寸L.W.H (mm)	重　量 (kg)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Suggested Pressure	Package Size	Weight
JM-120H	20-99999	98	170	400	110/220	50/60	0.7	0.3-0.4	560x420x405	16/21



JM-120HLR/G

电脑切带机（冷、热红外）

Label Cutter (Cold & Hot)





功能特性：
高速：每分钟可切断 170 片。(以 50mm 长度为例)
高精度：光电感应器可准确的捕捉商标的切断线，从而精确的控制每次的有效切断长度。
切断面平整：刀刃由优质进口钢材制成，使用寿命长。热刀可对彩色丝带、编织带的切断面进行热封，且封口平整无毛边。
切刀次数：可设置多次切断，以达到切断的效果。
切刀速度：对于厚料且不容易切断的材料，可调节切刀速度，以达到材料的切断效果。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换，页面功能直观易操作，设定方便。
补偿功能：因材料不同，切出的效果与输入尺寸不符时，只需输入实际切出的尺寸数值，系统自动补偿误差值。
故障自检：切刀传感器出错，无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。

可切断材质：
尼龙商标、织带、彩色缎带、背包带等尼龙材质。

Special features:
High speed: It can cut 170 pcs per minute. (50 mm long)
Accuracy: A sensor makes cut-length accurate by automatic sensing at set-position.
Cutting type: Melting & cutting by hot knife, woven label is cut neatly without fraying but not for heavy materials and installed with anti-static electricity device.
Cutting times:It can set quantity cutting times to achieve good quality cut.
Cutter speed:It can set the cutter speed for some thick and strong materials to achieve cutting effective.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation：After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.

Applications:
Woven label, printed label, ribbon tape, bag band etc.

型　号 Model	切断长度(mm) Cutting Length	最大切断宽度(mm) Max. Cutting Width	切断速度(p/min) Cutting Speed	刀片最高温度(℃) Max. Blade Temp	电压(v) Voltage	频率(Hz) Frequency	额定功率(kw) Power	建议气压(mpa) Suggested Pressure	包装尺寸L.W.H(mm) Package Size	重　量(kg) Weight
JM-120HLR	10-99999	100	170	350	110/220	50/60	0.7	0.3-0.4	560x420x405	16/21
JM-120HLR-G	10-99999	145	170	350	110/220	50/60	0.9	0.3-0.4	620x570x490	18/30

JM-120LR

电脑切带机（冷、热）

Auto-belt Loop Cutter (Cold & Hot)





功能特性：
高速：每分钟可切断 120 片。(以 50mm 长度为例)
高精度：采用高精度步进电机驱动，以保证每次操作的高精确性。
切断面平整：刀刃由优质进口钢材制成，使用寿命长。热刀可对彩色丝带、编织带的切断面进行热封，且封口平整无毛边。
切刀次数：可设置多次切断，以达到切断的效果。
切刀速度：对于厚料且不容易切断的材料，可调节切刀速度，以达到材料的切断效果。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换，页面功能直观易操作，设定方便。
补偿功能：因材料不同，切出的效果与输入尺寸不符时，只需输入实际切出的尺寸数值，系统自动补偿误差值。
故障自检：切刀传感器出错，无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。
自动操作、自动暂停：只需设定您所需的切断长度和数量，其余工作都自动完成。一旦材料用完，机器将自动停止工作。

可切断材质：
编织带、尼龙织带、彩色缎带、背包带等尼龙材质。

Special features:
High speed: It can cut 120 pcs per minute. (50 mm long)
Accuracy: Cut-length is accurate owing to a stepping motor.
Cutting type: Melting & cutting by hot knife, woven label is cut neatly without fraying but not for heavy materials and installed with anti-static electricity device.
Cutting times:It can set quantity cutting times to achieve good quality cut.
Cutter speed:It can set the cutter speed for some thick and strong materials to achieve cutting effective.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate , setting is convenient.
Compensation：After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Automatic operation、Automatic stopper: It works automatically only by setting speed length quantity and temperature.It stops automatically if materials run out during operation.

Applications:
Belt loop, bag band, shrink tube, string, elastic band, plastic zipper etc.

型　号 Model	切断长度(mm) Cutting Length	最大切断宽度(mm) Max. Cutting Width	切断速度(p/min) Cutting Speed	刀片最高温度(℃) Max. Blade Temp	电压(v) Voltage	频率(Hz) Frequency	额定功率(kw) Power	包装尺寸L.W.H(mm) Package Size	重　量(kg) Weight
JM-120LR	20-99999	100	120	350	110/220	50/60	0.75	560x420x405	24/29

JM-120L

电脑切带机（冷刀）

Cold Knife Cutter

功能特性：
高速：每分钟可切断 110 片。(以 50mm 长度为例)
高精度：采用高精度电机驱动，以保证每次操作的高精确性。
切断面平整：刀刃由优质进口钢材制成，使用寿命长。
切刀次数：可设置多次切断，以达到切断的效果。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换，页面功能直观易操作，设定方便。
补偿功能：因材料不同，切出的效果与输入尺寸不符时，只需输入实际切出的尺寸数值，系统自动补偿误差值。
故障自检：切刀传感器出错，无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。
自动操作、自动暂停：只需设定您所需的切断长度和数量，其余工作都自动完成。一旦材料用完，机器将自动停止工作。

可切断材质：
编织带、魔术贴、塑料软管、鞋带、塑料拉链、电脑排线等。

Special features:
High speed: It can cut 110 pcs per minute. (50 mm long)
Accuracy: Cut-length is accurate owing to a motor.
Cutting type: Cutting is neat due to using a cold cutter thich is durable because they are made of high-speed steel.
Cutting times:It can set quantity cutting times to achieve good quality cut.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation：After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Automatic operation、Automatic stopper: It works automatically only by setting speed length quantity and temperature.It stops automatically if materials run out during operation.

Applications:
Belt loop, soft tube, string, plastic zipper, elastic band, small webbing etc.

型　号 Model	切断长度(mm) Cutting Length	最大切断宽度(mm) Max. Cutting Width	切断速度(p/min) Cutting Speed	刀片最高温度(℃) Max. Blade Temp	电压(v) Voltage	频率(Hz) Frequency	额定功率(kw) Power	包装尺寸L.W.H(mm) Package Size	重　量(kg) Weight
JM-120L	20-99999	105	110	-	110/220	50/60	0.35	560x420x405	24/27



JM-120R

电脑切带机（圆角）

Velcro Tape Round Shape Cutter





功能特性：
高速：每分钟可切断 80 片。(以 50mm 长度为例)
高精度：采用高精度电机驱动，以保证每次操作的高精确性。
切断面平整：刀刃由优质进口钢材制成，使用寿命长。
切刀次数：可设置多次切断，以达到切断的效果。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换，页面功能直观易操作，设定方便。
补偿功能：因材料不同，切出的效果与输入尺寸不符时，只需输入实际切出的尺寸数值，系统自动补偿误差值。
故障自检：切刀传感器出错，无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。
自动操作、自动暂停：只需设定您所需的切断长度和数量，其余工作都自动完成。一旦材料用完，机器将自动停止工作。

可切断材质：
魔术贴。

Special features:
High speed: It can cut 80 pcs per minute. (50 mm long)
Accuracy: Cut-length is accurate owing to a motor.
Cutting type: Cutting is neat due to using a cold cutter thich is durable because they are made of high-speed steel.
Cutting times:It can set quantity cutting times to achieve good quality cut.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation：After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Automatic operation、Automatic stopper: It works automatically only by setting speed length quantity and temperature.It stops automatically if materials run out during operation.

Applications:
Velcro tapes.

型　号 Model	切断长度(mm) Cutting Length	最大切断宽度(mm) Max. Cutting Width	切断速度(p/min) Cutting Speed	刀片最高温度(℃) Max. Blade Temp	电压(v) Voltage	频率(Hz) Frequency	额定功率(kw) Power	包装尺寸L.W.H(mm) Package Size	重　量(kg) Weight
JM-120R	20-99999	10-50	80	-	110/220	50/60	0.35	560x420x405	24/29



JM-120H



JM-120H/300M

电脑切带机（热刀）配送带装置

Hot Knife Cutter With Auto-feeder



功能特性：
高速：每分钟可切断 120 片。(以 50mm 长度为例)
高精度：采用高精度步进电机驱动，以保证每次操作的高精确性。
切断面平整：刀刃由优质进口钢材制成，使用寿命长。热刀可对彩色丝带、编织带的切断面进行热封，且封口平整无毛边。
切刀次数：可设置多次切断，以达到切断的效果。
切刀速度：对于厚料且不容易切断的材料，可调节切刀速度，以达到材料的切断效果。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换，页面功能直观易操作，设定方便。
补偿功能：因材料不同，切出的效果与输入尺寸不符时，只需输入实际切出的尺寸数值，系统自动补偿误差值。
故障自检：切刀传感器出错，无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。
送带装置：采用红外传感器控制，根据主机的工作速度自动调节送带速度。预放转送橡筋，使其保持统一的张力，可确保切断长度的准确性。

可切断材质：
松紧带、编织带、尼龙织带、彩色缎带、背包带等尼龙材质。

Special features:
High speed: It can cut 120 pcs per minute. (50 mm long)
Accuracy: Cut-length is accurate owing to a stepping motor.
Cutting type: Melting & cutting by hot knife, woven label is cut neatly without fraying but not for heavy materials and installed with anti-static electricity device.
Cutting times:It can set quantity cutting times to achieve good quality cut.
Cutter speed:It can set the cutter speed for some thick and strong materials to achieve cutting effective.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation：After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Auto-feeding machine: for multi-purpose pre-feeding, especially for heavier and elastic material, it is applicable for auto-cutting machine. Pre-feeding device to keep a constant tension of elastic band for correct length.

Applications:
Wolven tapes, ribbon tape, bag band, webbing etc.

型　号 Model	切断长度(mm) Cutting Length	最大切断宽度(mm) Max. Cutting Width	切断速度(p/min) Cutting Speed	刀片最高温度(℃) Max. Blade Temp	电压(v) Voltage	频率(Hz) Frequency	额定功率(kw) Power	包装尺寸L.W.H(mm) Package Size	重　量(kg) Weight
JM-120H	20-99999	98	120	420	110/220	50/60	0.75	560x420x405	24/29



JM-120HX

电脑切带机（斜角/直角）

Hot Knife Cutter (Bevel / Straight)





功能特性：
高速：每分钟可切断 120 片。(以 50mm 长度为例)
高精度：采用高精度步进电机驱动，以保证每次操作的高精确性。
切断面平整：刀刃由优质进口钢材制成，使用寿命长。热刀可对彩色丝带、编织带的切断面进行热封，且封口平整无毛边。
裁切形状：刀具可手动调整角度，从而完成斜角切断。
切刀次数：可设置多次切断，以达到切断的效果。
切刀速度：对于厚料且不容易切断的材料，可调节切刀速度，以达到材料的切断效果。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换，页面功能直观易操作，设定方便。
补偿功能：因材料不同，切出的效果与输入尺寸不符时，只需输入实际切出的尺寸数值，系统自动补偿误差值。
故障自检：切刀传感器出错，无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。

可切断材质：
尼龙商标、织带、彩色缎带、背包带等尼龙材质。

Special features:
High speed: It can cut 120 pcs per minute. (50 mm long)
Accuracy: Cut-length is accurate owing to a stepping motor.
Cutting type: Melting & cutting by hot knife, woven label is cut neatly without fraying but not for heavy materials and installed with anti-static electricity device.
Cutting shapes: Cutting bevel is adjusted by hand.
Cutting times:It can set quantity cutting times to achieve good quality cut.
Cutter speed:It can set the cutter speed for some thick and strong materials to achieve cutting effective.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation：After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.

Applications:
Belt loop, ribbon tape, bag band, small webbing etc.

型　号 Model	切断长度(mm) Cutting Length	最大切断宽度(mm) Max. Cutting Width	切断速度(p/min) Cutting Speed	刀片最高温度(℃) Max. Blade Temp	电压(v) Voltage	频率(Hz) Frequency	额定功率(kw) Power	包装尺寸L.W.H(mm) Package Size	重　量(kg) Weight
JM-120HX	20-99999	35/55	120	420	110/220	50/60	1.15	560x420x405	24/29



JM-120HL

电脑切带机（冷刀红外）

Label Cold Knife Cutter





功能特性：
高速：每分钟可切断 120 片。（以 50mm 长度为例）
高精度：光电感应可准确捕捉商标的切断线，从而精确的控制每次的有效切断长度。
切断面平整：刀刃由优质进口钢材制成，保证了切断面的平整性。
切刀次数：可设置多次切断，以达到切断的效果。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换，页面功能直观易操作，设定方便。
补偿功能：因材料不同，切出的效果与输入尺寸不符时，只需输入实际切出的尺寸数值，系统自动补偿误差值。
故障自检：切刀传感器出错，无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。

可切断材质：
商标、编织带、魔术贴、塑料软管、鞋带、塑料拉链、电脑排线。

Special features:
High speed: It can cut 120 pcs per minute. (50 mm long)
Accuracy: A sensor makes cut-length accurate by automatic sensing at set-position.
Cutting type: Cutting is neat due to using a cold cutter which is durable because they are made of high-speed steel.
Cutting times:It can set quantity cutting times to achieve good quality cut.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation: After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.

Applications:
Woven label, printed label, ribbon tape, bag band, etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度 (p/min)	刀片最高温度 (℃)	电压 (v)	频率 (Hz)	额定功率 (kw)	包装尺寸 L.W.H (mm)	重　量 (kg)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Package Size	Weight
JM-120HL	20-99999	105	120	-	110/220	50/60	0.35	560x420x405	24/27

JM-120HLR

电脑切带机（冷、热红外）

Label Cutter (Cold & Hot)





功能特性：
高速：每分钟可切断 120 片。（以 50mm 长度为例）
高精度：光电感应可准确捕捉商标的切断线，从而精确的控制每次的有效切断长度。
切断面平整：刀刃由优质进口钢材制成，使用寿命长。热刀可对彩色丝带、编织带的切断面进行热封，且封口平整无毛边。
切刀次数：可设置多次切断，以达到切断的效果。
切刀速度：对于厚料且不容易切断的材料，可调节切刀速度，以达到材料的切断效果。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换，页面功能直观易操作，设定方便。
补偿功能：因材料不同，切出的效果与输入尺寸不符时，只需输入实际切出的尺寸数值，系统自动补偿误差值。
故障自检：切刀传感器出错，无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。

可切断材质：
尼龙商标、织带、彩色缎带、背包带等尼龙材质。

Special features:
High speed: It can cut 120 pcs per minute. (50 mm long)
Accuracy: A sensor makes cut-length accurate by automatic sensing at set-position.
Cutting type: Melting & cutting by hot knife, woven label is cut neatly without fraying but not for heavy materials and installed with anti-static electricity device.
Cutting times:It can set quantity cutting times to achieve good quality cut.
Cutter speed:It can set the cutter speed for some thick and strong materials to achieve cutting effective.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation: After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.

Applications:
Woven label, printed label, ribbon tape, bag band etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度 (p/min)	刀片最高温度 (℃)	电压 (v)	频率 (Hz)	额定功率 (kw)	包装尺寸 L.W.H (mm)	重　量 (kg)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Package Size	Weight
JM-120HLR	20-99999	100	120	350	110/220	50/60	0.75	560x420x405	24/29



JM-120SH

电脑切带机（热刀红外）

Auto-Label Hot Knife Cutter





功能特性：
高速：每分钟可切断 120 片。（以 50mm 长度为例）
高精度：光电感应可准确捕捉商标的切断线，从而精确的控制每次的有效切断长度。
切断面平整：刀刃由优质进口钢材制成，使用寿命长。热刀可对彩色丝带、编织带的切断面进行热封，且封口平整无毛边。
切刀次数：可设置多次切断，以达到切断的效果。
切刀速度：对于厚料且不容易切断的材料，可调节切刀速度，以达到材料的切断效果。
PLC 控制触摸屏系统：采用 PLC 系统、触摸屏多种语言转换，页面功能直观易操作，设定方便。
补偿功能：因材料不同，切出的效果与输入尺寸不符时，只需输入实际切出的尺寸数值，系统自动补偿误差值。
故障自检：切刀传感器出错，无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。

可切断材质：
尼龙商标、织带、彩色缎带、背包带等尼龙材质。

Special features:
High speed: It can cut 120 pcs per minute. (50 mm long)
Accuracy: A sensor makes cut-length accurate by automatic sensing at set-position.
Cutting type: Melting & cutting by hot knife, woven label is cut neatly without fraying but not for heavy materials and installed with anti-static electricity device.
Cutting times:It can set quantity cutting times to achieve good quality cut.
Cutter speed:It can set the cutter speed for some thick and strong materials to achieve cutting effective.
Touch panel control system:Adopt PLC system,multilingual conversion by the touch panel ,the page of function is intuitive and easy operate ,setting is convenient.
Compensation: After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.

Applications:
Woven label, printed label, ribbon tape, bag band etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度 (p/min)	刀片最高温度 (℃)	电压 (v)	频率 (Hz)	额定功率 (kw)	包装尺寸 L.W.H (mm)	重　量 (kg)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Package Size	Weight
JM-120SH	20-99999	98	120	420	110/220	50/60	0.75	560x420x405	24/29



JM-110LR

电脑切带机（冷、热）

Economic Belt Loop Cutter (Cold & Hot)





功能特性
高速：每分钟可切断 95 片。（以 50mm 长度为例）
高精度：采用高精度步进电机驱动，以保证每次操作的高精确性。
切断面平整：热刀可对彩色丝带、轻薄编织带的切断面进行高温热封，且封口平整无毛边，刀刃由进口优质钢材制成，　使用寿命长。
自动操作：只需设定您所需的切断速度、长度、数量和温度，其余工作都自动完成；一旦材料用完，将自动停止工作。
补偿功能：只需输入实际切出的尺寸数值，便可准确切出系统设置的长度。
故障自检：切刀传感器出错、无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。
记忆功能：在开关关闭前，自动存储所设置的切断长度和切断数量以及切断速度等。

可切断材质：
编织带、尼龙织带、彩色缎带、背包带等尼龙材质。

Special features:
High speed: It can cut 95 pcs per minute. (50 mm long)
Accuracy: Cut-length is accurate owing to a stepping motor.
Cutting type: Melting & cutting by hot knife, tapes are cut neatly without fraying and installed with anti-static electricity device.
Automatic operation: It works automatically only by setting speed length quantity and temperature. It stops automatically if materials run out during operation.
Compensation: After actual length data inputted, accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Memory: Set-length, set-q' ty & set-speed are not erased even if power off & on.

Applications:
Belt loop, bag band, shrink tube, string, elastic band, plastic zipper etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度 (p/min)	刀片最高温度 (℃)	电压 (v)	频率 (Hz)	额定功率 (kw)	包装尺寸 L.W.H (mm)	重　量 (kg)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Package Size	Weight
JM-110LR	20-9999	95	95	350	110/220	50/60	0.64	560x420x405	17/22



JM-110H

电脑切带机（热刀）

Economic Hot Knife Cutter





功能特性
高速：每分钟可切断 95 片。（以 50mm 长度为例）
高精度：采用高精度步进电机驱动，以保证每次操作的高精确性。
切断面平整：热刀可对彩色丝带、轻薄编织带的切断面进行高温热封，且封口平整无毛边，刀刃由进口优质钢材制成，　使用寿命长。
自动操作：只需设定您所需的切断速度、长度、数量和温度，其余工作都自动完成；一旦材料用完，将自动停止工作。
补偿功能：只需输入实际切出的尺寸数值，便可准确切出系统设置的长度。
故障自检：切刀传感器出错、无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。
记忆功能：在开关关闭前，自动存储所设置的切断长度和切断数量以及切断速度等。

可切断材质：
编织带、尼龙织带、彩色缎带、背包带等尼龙材质。

Special features:
High speed: It can cut 95 pcs per minute. (50 mm long)
Accuracy: Cut-length is accurate owing to a stepping motor.
Cutting type: Melting & cutting by hot knife, tapes are cut neatly without fraying and installed with anti-static electricity device.
Automatic operation: It works automatically only by setting speed length quantity and temperature. It stops automatically if materials run out during operation.
Compensation: After actual length data inputted, accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Memory: Set-length, set-q' ty & set-speed are not erased even if power off & on.

Applications:
Belt loop, bag band, shrink tube, string, elastic band, plastic zipper etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度 (p/min)	刀片最高温度 (℃)	电压 (v)	频率 (Hz)	额定功率 (kw)	包装尺寸 L.W.H (mm)	重　量 (kg)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Package Size	Weight
JM-110H	20-9999	100	95	420	110/220	50/60	0.64	560x420x405	17/22



JM-110L

电脑切带机（冷刀）

Economic Cold Knife Cutter





功能特性
高速：每分钟可切断 95 片。（以 50mm 长度为例）
高精度：采用高精度步进电机驱动，以保证每次操作的高精确性。
切断面平整：刀刃由进口钢材制成，保证了切断面的平整性。
自动操作：只需设定您所需的切断速度、长度、数量，其余工作都自动完成；一旦材料用完，将自动停止工作。
补偿功能：只需输入实际切出的尺寸数值，便可准确切出系统设置的长度。
故障自检：切刀传感器出错、无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。
记忆功能：在开关关闭前，自动存储所设置的切断长度和切断数量以及切断速度等。

可切断材质：
编织带、魔术贴、塑料软管、鞋带、塑料拉链、电脑排线等。

Special features:
High speed: It can cut 95 pcs per minute. (50 mm long)
Accuracy: Cut-length is accurate owing to a stepping motor.
Cutting type: Cutting is neat due to using a cold cutter which is durable because they are made of high-speed steel.
Automatic operation: It works automatically only by setting speed、length、quantity. It stops automatically if materials run out during operation.
Compensation: After actual length data inputted, accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Memory: Set-length, set-q' ty & set-speed are not erased even if power off & on.

Applications:
Belt loop, soft tube, string, plastic zipper, elastic band, small webbing etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度 (p/min)	刀片最高温度 (℃)	电压 (v)	频率 (Hz)	额定功率 (kw)	包装尺寸 L.W.H (mm)	重　量 (kg)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Package Size	Weight
JM-110L	20-9999	105	95	-	110/220	50/60	0.26	560x420x405	17/22



JM-110HLR

电脑切带机（冷、热红外）

Economic Label Cutter (Cold & Hot)





功能特性：
高速：每分钟可切断 95 片。（以 50㎜ 长度为例）
高精度：光电感应器可准确的捕捉商标的切断线，从而精确的控制每次的有效切断长度。
切断面平整：热刀可对彩色丝带、轻薄编织带的切断面进行高温热封，且封口平整无毛边，刀刃由进口优质钢材制成， 使用寿命长。
自动操作：只需设定您所需的切断速度、长度、数量和温度，其余工作都自动完成；一旦材料用完，将自动停止工作。
补偿功能：只需输入实际切出的尺寸数值，便可准确切出系统设置的长度。
故障自检：切刀传感器出错、无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。
记忆功能：在开关关闭前，自动存储所设置的切断长度和切断数

可切断材质：
编织带、尼龙织带、彩色缎带、背包带等尼龙材质。

Special features:
High speed: It can cut 95 pcs per minute. (50 mm long)
Accuracy: A sensor makes cut-length accurate by automatic sensing at set-position.
Cutting type: Melting & cutting by hot knife, tapes are cut neatly without fraying and installed with anti-static electricity device.
Automatic operation: It works automatically only by setting speed length quantity and temperature.It stops automatically if materials run out during operation.
Compensation： After actual length data inputted,accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Memory: Set-length, set-q'ty & set-speed are not erased even if power off & on.

Applications:
Belt loop, bag band, shrink tube, string, elastic band, plastic zipper etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度 (p/min)	刀片最高温度 (℃)	电压 (v)	频率 (Hz)	额定功率 (kw)	包装尺寸 L.W.H (mm)	重　量 (kg)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Package Size	Weight
JM-110HLR	20-9999	95	95	350	110/220	50/60	0.64	560x420x405	17/22



JM-110R

电脑切带机（圆角）

Economic Velcro Tape Round Cutter





功能特性：
高速：每分钟可切断 95 片。（以 50㎜ 长度为例）
高精度：采用高精度步进电机驱动，以保证每次操作的高精确性。
切断面平整：刀刃由进口钢材制成，保证了切断面的平整性。
自动操作：只需设定您所需的切断速度、长度、数量，其余工作都自动完成；一旦材料用完，将自动停止工作。
补偿功能：只需输入实际切出的尺寸数值，便可准确切出系统设置的长度。
故障自检：切刀传感器出错、无材料供给，一旦出现故障，系统将自动在屏幕上显示出错代码。
记忆功能：在开关关闭前，自动存储所设置的切断长度和切断数量以及切断速度等。

可切断材质：
魔术贴。

Special features:
High speed: It can cut 95 pcs per minute. (50 mm long)
Accuracy: Cut-length is accurate owing to a stepping motor.
Cutting type: Cutting is neat due to using a cold cutter which is durable because they are made of high-speed steel.
Automatic operation: It works automatically only by setting speed、length、quantity. It stops automatically if materials run out during operation.
Compensation: After actual length data inputted, accurately cut out the length meet the system settings.
Fault self-check:cutting sensor error,no supply,the error code will show on the system panel directly if the fault happened.
Memory: Set-length, set-q' ty & set-speed are not erased even if power off & on.

Applications:
Velcro tapes.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度 (p/min)	刀片最高温度 (℃)	电压 (v)	频率 (Hz)	额定功率 (kw)	包装尺寸 L.W.H (mm)	重　量 (kg)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Max. Blade Temp	Voltage	Frequency	Power	Package Size	Weight
JM-110R	20-9999	10-50	95	-	110/220	50/60	0.26	560x420x405	17/22



JM-300S

电脑送带机

Tape Feeder

功能特性：
全自动电脑送带机是一种应用于各种切带机、缝纫机等新型的多功能送带机。采用微动开关装置，可根据主机的工作速度自动开启送带开关。适用于不同宽度、尺寸的编织带、松紧带、商标等带状物品。当不成卷的橡筋、商标等直接放置于盒内或地上送料时，该装置可防止橡筋、商标等扭曲、缠绕。具有用途广、操作简单等特点，是提高生产效率、提高产品质量、节省人工的首选。

Special features:
Feeding machine, this device is for multi-purpose pre-feeding, easy operation.It support the use for cutting machine、sewing machine etc. Adopt micro switch device, could according to the main machine working speed to working feeding function automatically. It suitable for different type width and thickness woven belt、elastic belts、labels etc. The anti intertwist device for make the belt untie and twisting.

型　号	送带速度 (mm)	最大送带宽度 (mm)	电机转度 (r/min)	电压 (v)	频率 (Hz)	包装尺寸 L.W.H (mm)	重　量 (kg)
Model	Feeding Speed	Max. Feeding Width	Motor Speed	Voltage	Frequency	Package Size	Weight
JM-300S	自动/Auto	100	1300	110/220	50/60	450x445x405	22

JEMA®
箭马中国切带机领先品牌之一
JEMA is a Top Brand of Cutting Machine in China



JM-300M

电脑送带机

Tape Feeder

功能特性：
全自动电脑送带机是一种应用于各种切带机、缝纫机等新型的多功能送带机。采用微动开关装置，可根据主机的工作速度自动开启送带开关。适用于不同宽度、尺寸的编织带、松紧带、商标等带状物品。当不成卷的橡筋、商标等直接放置于盒内或地上送料时，该装置可防止橡筋、商标等扭曲、缠绕。具有用途广、操作简单等特点，是提高生产效率、提高产品质量、节省人工的首选。

Special features:
Feeding machine, this device is for multi-purpose pre-feeding, easy operation.It support the use for cutting machine、sewing machine etc. Adopt micro switch device, could according to the main machine working speed to working feeding function automatically. It suitable for different type width and thickness woven belt、elastic belts、labels etc. The anti intertwist device for make the belt untie and twisting.

型　号	送带速度 (mm)	最大送带宽度 (mm)	电机转度 (r/min)	电压 (v)	频率 (Hz)	包装尺寸 L.W.H (mm)	重　量 (kg)
Model	Feeding Speed	Max. Feeding Width	Motor Speed	Voltage	Frequency	Package Size	Weight
JM-300M	自动/Auto	140	1500	110/220	50/60	560x415x400	14



JM-815



JM-817

JM-815/817

切带机（冷、热刀）

Belt Cutter (Cold & Hot)







功能特性：
适用于鞋、帽、箱包，是服装生产、线带加工、电器装配等行业的配套设备。可任意调节送料长度，具备自动进料计数功能，工效高、噪音低、体积小、重量轻、操作方便等特点。

可切断材质：
编织带、魔术贴、塑料软管、鞋带、塑料拉链、电脑排线。

Special features:
It is a mechincal tape cutting machine. for clothing production lines with soft matericals, electrical equipment assembly industries.
Feeding can arbitrarily adjust the length of the counting function with automatic feed, higher efficiency, low noise, small size and light weight. easy to operate and so on.

Applications:
Woven tapes, soft tube, string, plastic zipper, small webbing etc.

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度 (p/min)	包装尺寸 L.W.H (mm)	重　量 (kg)	装箱率 (台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Package Size	Weight	Loading Rate Pic
JM-815	15-1500	50	23-35	500x340x455	23	1
JM-817	15-1500	60	23-35	500x340x455	23	1



JM-818

切带机（圆角）

Velcro Tape Cutter (Round)





功能特性：
可切断圆角、椭圆、整圆等形状。是服装生产、线带加工、电器装配等行业的配套设备。
可任意调节送料长度，具备自动进料计数功能，工效高、噪音低、体积小、重量轻、操作方便等特点。

可切断材质：
魔术贴。

Special features:
It is specially designed for round velcro tape that need cetfillet. Feeding length can be freely adjusted, it has the length of the counting function with automatic feed, higher efficiency, low noise, small size and light weight, easy to operate.

Applications:
Velcro tapes

型　号	切断长度 (mm)	最大切断宽度 (mm)	切断速度 (p/min)	包装尺寸 L.W.H (mm)	重　量 (kg)	装箱率 (台)
Model	Cutting Length	Max. Cutting Width	Cutting Speed	Package Size	Weight	Loading Rate Pic
JM-818	15-1500	25	23-35	500x340x455	23	1



JM-600V/600VD

魔术贴自动送料机（悬空送料/下送料）

Auto-Velcro Feeding Machine (Upper feeder / Lower feeder)



功能特性：

1、采用 PLC 触摸屏操作系统，软件更稳定，页面更直观。

2、学习：在送料机臂对套结机压脚位置时，按下“学习”键，再按◄—键送料机臂移到对齐套节机机针中心，如移过了按键—►退回，对好后再按确认键。送料距离自动调节好。调节速度快。

3、补偿：因材料不同，切出来的材料可能会与输入的参数不符，按下补偿键，输入切出来的实际尺寸，误差尺寸机器自动调整。

4、吹气：在切带时往下吹气，使材料不会往上翘，方便机臂压料。

5、送料机臂：采用步进电机送料，送料速度快、送料精度高，噪音低、调整送料距离快。（专利产品）

6、刀片、刀模互换：根据需要直角刀片可以直接换成切圆角的刀模。

7、压料轮：采用双气缸一键开关设计，只需一按开关，压料轮自动抬起，轻松取、放魔术贴。

8、输料导轨：采用前后双滑块设计，刚劲更强，移动更顺滑、输料更精准。

9、整机一体式设计：采用机械、电控一体设计，具有整体体积小，接线简单、安装方便。

10、多重安全防护：防碰撞功能；手动送料防碰撞；布料取出防碰撞。

适用范围：魔术贴。

通过更换刀模可实现圆角、直角以及不同角度的缝制，应用范围广，送料速度快，调节方便。魔术贴送入卡槽不容易掉出来等优点。广泛应用于反光服，箱包，地毯，冲锋衣，帐篷等工厂。

Special features:

1. Adopting a PLC touch screen operating system, the software is more stable and the pages are more intuitive.
2. Learn: When the feed arm is aligned with the bartack sewing machine, press this key, and then press the key ◄— to move the feed arm to the needle center of the bartack sewing machine. If it over-travels, press the key —► to move it back. After it is well aligned, press the OK key. The feeding distance can be automatically adjusted fast.
3. Compensation: As there are different materials, the cut material may be inconsistent with the input parameters. Press the Compensation key, and input the cut size; the machine will adjust the length automatically.
4. Blowing: Blow down when cutting the belt, so that the material will not warp up, which is convenient for the machine arm to press the material.
5. Feeder arm: adopts stepping motor for feeding, with fast feeding speed, high feeding accuracy, low noise and fast adjustment of feeding distance. (patented products)
6. Interchange of knife die and cutter die: The right-angle blade can be directly replaced with a cutter die for cutting round corners as required.
7. Material pressing wheel: Adopting a dual cylinder one button switch design, with just one press of the switch, the material pressing wheel automatically lifts, making it easy to take and release Velcro.
8. Feeding guide rail: Adopting a front and rear double slider design, it has stronger rigidity, smoother movement, and more accurate feeding.
9. The whole machine integrated design: It adopts mechanical and electric control integrated; design, with small overall volume, simple wiring and convenient installation.
10. Multiple security protection: Anti collision function; Manual feeding for collision prevention; Fabric removal for collision prevention.

Applications: Velcro tapes

The round, right and different angles can be sewn by replacing the cutter die, so that a wide range of applications, high feeding speed and user-friendly adjustment can be achieved. The material can be fed into the slot with the Velcro, which is not easy to fall out. It is widely used in the factories of reflective clothing, luggage, carpets, jackets, tents and so on.



冲锋衣、作训服等服装
Clothing such as assault suits and training uniforms



车类用品
Car supplies



箱包鞋帽
Luggage, shoes, hats



医疗用品
Medical supplies

技术参数 Technical Parameter

型号	送料长度 (mm)	送料宽度 (mm)	送料行程 (mm)	送料速度 (P/min)	标准气压 (Mpa)	刀片切断宽度(mm)	刀模：圆角/直角宽度(mm)	电压 (V)	功率 (W)	频率 (Hz)	包装尺寸 (mm)	毛重 (KG)
Model	Feeding Length	Feeding Width	Feeding Stroke	Feeding Speed	Air Pressure	Cutting Width	Blade Mold: Round /Right angle width	Voltage	Power	Frequency	Package Size	Weight
JM-600V(悬空送料)	20-999	50	300	60	0.35-0.45	10-50	15-40/15-50	110/220	60	50/60	620x540x520	42
JM-600V-2210	40-190	20-50	300	40	0.35-0.45	10-50	20-40/20-50	110/220	60	50/60	1400x880x1330	252
JM-600V-3520	40-290	20-55	300	30	0.35-0.45	10-50	20-40/20-50	110/220	60	50/60	1800x1310x1320	340
JM-600V-3020	40-290	20-50	300	30	0.35-0.45	10-50	20-40/20-50	110/220	60	50/60	1800x1310x1320	340
JM-600V-1310	30-120	20-50	300	40	0.35-0.45	10-50	20-40/20-50	110/220	60	50/60	1250x830x1330	212
JM-600VD(下送料)	20-999	50	300	60	0.35-0.45	10-50	15-40/15-50	110/220	60	50/60	620x540x520	42
JM-600VD-0906	20-80	15-50	260	35	0.35-0.45	10-50	15-40/15-50	110/220	60	50/60	1290x820x1330	163
JM-600VD-1900	20-40	15-30	230	35	0.35-0.45	10-50	15-30/15-50	110/220	60	50/60	1220x920x1350	170
JM-600VD-430	20-40	15-30	230	35	0.35-0.45	10-50	15-30/15-50	110/220	60	50/60	1300x1330x820	157

JEMA®
箭马中国切带机领先品牌之一
JEMA is a Top Brand of Cutting Machine in China



配2210花样机
With 2210 pattern machine

功能特性：

1、采用 PLC 触摸屏操作系统，软件更稳定，页面更直观。

2、学习：独特的软件设计，在送料机臂对花样机压布框位置时，按下“学习”键，再按—►键送料槽移到花样机压布框里面（魔术贴尾部靠近压布框边缘），如移过了按◄—键退回，对好后再按确认键。送料距离自动调节好。调节速度快。

3、补偿：因材料不同，切出来的材料可能会与输入的参数不符，按下补偿键，输入切出来的实际尺寸，误差尺寸机器自动调整。

4、吹气：在切带时往下吹气，使材料不会往上翘，方便机臂压料。

5、送料机臂：采用步进电机送料，送料速度快、送料精度高，噪音低、调整送料距离快。（专利产品）

6、输料槽：输料槽根据魔术贴缝制长短可更换、魔术贴尺寸宽、窄可调。

7、悬空送料：独特设计的魔术贴悬空送料装置，在缝制时先放布料精准定位（避免缝制区域移位），再送魔术贴精准缝制。（专利产品）

8、压布框宽窄可调：只要松开压布框上的左右压板螺丝，根据实际宽度前后移动，固紧螺丝即可，方便快捷。特别对兜盖、门禁等窄边缝制要求的。

9、刀片、刀模互换：根据需要直角刀片可以直接换成切圆角的刀模。

10、压料轮：采用双气缸一键开关设计，只需一按开关，压料轮自动抬起，轻松取、放魔术贴。

11、输料导轨：采用前后双滑块设计，刚劲更强，移动更顺滑、输料更精准。

12、侧滑压料：输料槽把魔术贴送到花样机压框上方，通过侧滑压料板压住魔术贴，进行缝制。

13、整机一体式设计：采用机械、电控一体设计，具有整体体积小，接线简单、安装方便。

14、多重安全防护：防碰撞功能；手动送料防碰撞；布料取出防碰撞。

适用范围：魔术贴。

通过更换刀模可实现圆角、直角以及不同角度的缝制，应用范围广，送料速度快，调节方便。魔术贴送入卡槽不容易掉出来等优点。广泛应用于反光服，箱包，地毯，冲锋衣，帐篷等工厂。

JM-600V

魔术贴自动送料机（悬空送料）

Auto-Velcro Feeding Machine(Upper feeder)



Special features:

1. Adopting a PLC touch screen operating system, the software is more stable and the pages are more intuitive.
2. Learn: Unique software design, press the "learn" button and then press the —► move the key feeding groove into the fabric pressing frame of the pattern machine (the end of the velcro is close to the edge of the fabric pressing frame), and if it has been moved, press the button ◄— to return, then press the confirm button after aligning. The feeding distance is automatically adjusted. Fast adjustment speed.
3. Compensation: As there are different materials, the cut material may be inconsistent with the input parameters. Press the Compensation key, and input the cut size; the machine will adjust the length automatically.
4. Blowing: Blow down when cutting the belt, so that the material will not warp up, which is convenient for the machine arm to press the material.
5. Feeder arm: adopts stepping motor for feeding, with fast feeding speed, high feeding accuracy, low noise and fast adjustment of feeding distance. (patented products)
6. Feeding groove: The feeding groove can be replaced according to the length of the velcro sewing, and the size of the velcro can be adjusted in width and width.
7. Upper feeding: A uniquely designed velcro suspended feeding device that accurately positions the fabric during sewing (to avoid shifting the sewing area), and then delivers velcro for precise sewing. (Patent products)
8. Adjustable width of the press frame: Simply loosen the left and right pressure plate screws on the press frame, move back and forth according to the actual width, and tighten the screws, which is convenient and fast. Special requirements for sewing narrow edges such as hood and access control.
9. Interchange of knife die and cutter die: The right-angle blade can be directly replaced with a cutter die for cutting round corners as required.
10. Material pressing wheel: Adopting a dual cylinder one button switch design, with just one press of the switch, the material pressing wheel automatically lifts, making it easy to take and release Velcro.
11. Feeding guide rail: Adopting a front and rear double slider design, it has stronger rigidity, smoother movement, and more accurate feeding.
12. Side sliding material pressing: The feeding groove sends the Velcro to the top of the pattern machine pressing frame, and uses the side sliding material pressing plate to press the Velcro and sew it.
13. The whole machine integrated design: It adopts mechanical and electric control integrated; design, with small overall volume, simple wiring and convenient installation.
14. Multiple security protection: Anti collision function; Manual feeding for collision prevention; Fabric removal for collision prevention.

Applications: Velcro tapes

The round, right and different angles can be sewn by replacing the cutter die, so that a wide range of applications, high feeding speed and user-friendly adjustment can be achieved. The material can be fed into the slot with the Velcro, which is not easy to fall out. It is widely used in the factories of reflective clothing, luggage, carpets, jackets, tents and so on.

JM-600V

魔术贴自动送料机（悬空送料）

Auto-Velcro Feeding Machine (Upper feeder)



配1310

JM-600VD

魔术贴自动送料机（下送料）

Auto-Velcro Feeding Machine (Lower feeder)



配0906

JM-600VD-FB

魔术贴自动送料机（下送料）-前后移

Auto-Velcro Feeding Machine (Lower feeder)-Move forward and backward



配430

JM-917/917-373D

自动送扣机（立扣）

Automatic Button Feeder (Shank Button)







功能特性：

1、采用 PLC 触摸屏操作系统，软件更稳定，页面更直观；
2、采用两种送扣模式：常规送扣、预送扣、根据需要自由转换，常规送扣：从输扣槽直接送到扣夹座。预送扣功能：打开“ 预送扣 ”，纽扣预送至送扣机与钉扣机中间待机（待机位置可设置），比常规送扣速度快；
3、独创的扣夹座带调节功能：轻松调节长柄、短柄位置，采用独特的仿钮扣轮廓设计的扣夹，夹扣更稳定。无需松开扣夹座螺丝重新安装，换扣更方便快捷。
4、震动盘自动升降功能：只需在界面按“ 震动盘升、震动盘降 ”，系统自动调节震动盘上下位置，调节方便快捷。
5、机臂纽扣扣柄长短调节：根据纽扣柄长短，通过调节螺丝根据实际要求快速调节，调节方便快捷；
6、扣夹挡扣：采用气缸挡扣模式，纽扣不跑偏，夹扣更稳固。
7、输扣槽 ：独特设计简洁高效的输扣槽采用底部、上部吹气，不卡扣送扣更顺畅 ，定时返吹装置：使纽扣不会堵在输扣槽进口处。
8、伺服电机：采用大功率伺服电机送扣，送扣速度快、震动小噪音低，送扣效率更高。
9、防碰撞功能：在操作时踩住脚踏不放连续送扣，不会出现机臂跟钉扣机扣夹相撞。

任意搭配：

该设备可搭配重机、兄弟款等各种品牌、型号的钉扣机，还可以搭配服装厂现有在使用的钉扣机上，大大节省了重新购买新钉扣机的费用。

Special features:

1.Adopt PLC touch screen operating system, more stable software, more intuitive page;
2.Adopt two feeding ways:normal feeding,advanced feeding,freely convert as needed.Normal feed:feeding buttons from begging to the end directly .Advanced feed:Turn on First,then set the ready position after the arm picks buttons.
3.Unique clip seat include adjustment function: adjust long-handle buttons,short-handle buttons easily. Adopt unique imitation button contour design buckle clip,buckle more stable,no need to loosen the buckle clamp screw to reinstall,buckle change more convenient and fast.
4.Vibrating disk up and down function: just press "Vibration disc up and down" on the interface, and the system will automatically adjust the up and down positions of the vibration disc, making adjustment convenient and fast.
5.Adjustment of the handle length of the arm button:according to the length of the handle it can be adjusted quickly and conveniently by adjusting screws according to the actual requirements.
6.Clamp blocker:adopt cylinder blockle mode,the button does not run off and the clop is more stable.
7.Feeding buckle track:Unique design simple and efficient track adopts bottom and upper air blowing,no stuck more smoothly feeding .Timing backblowing device:the buttons will not be blocked at the inlet of the feeding track.
8.Servo motor:Adopt big power servo motor control, high speed ,no noisy,higher efficient.
9.Anti-collision function: when operating,step on the foot pedal and do not release, the machine continuous feeding buttons, the arm of the machine will not collide with the buckle clip of the sewing head.

型　号	额定钉扣速度(pcs/min)	连续送扣速度(pcs/min)	送扣稳定性	纽扣直径(mm)	纽扣厚度(mm)	额定总功率(W)	建议气压(Mpa)	包装尺寸L.W.H(mm)	重　量(kg)
Model	Rated Button Sewing Speed	Continuous Button Feeding Speed	Button Feeding Stability	Button Diameter	Button Thickness	Rated Power	Suggested Air Pressure	Package Size	Weight
JM-917	40-50	60-65	99.7%	10-30	10	800	0.40-0.55	620x540x510	47
JM-917-373D	40-50	60-65	99.7%	10-30	10	800	0.40-0.55	1230x740x1330	130

JM-917S/917S-4-2

logo识别自动送扣机（立扣）

Automatic Button Feeder(LOGO、Shank Button)







功能特性：

1、一机双用：只需轻按 LOGO 开 / 关就能轻松转换 LOGO 识别与常规扣的送扣模式。
2、认字系统 ：把扣子上有 LOGO 的图案通过识别系统转换到您想要的方向如：（上下 LOGO 或左右 LOGO）使钉出来的服装纽扣的 LOGO 都朝同一方向。
3、采用 PLC 触摸屏操作系统，软件更稳定，页面更直观；
4、采用两种送扣模式：常规送扣、预送扣、根据需要自由转换，常规送扣：从输扣槽直接送到扣夹座。预送扣功能：打开“ 预送扣 ”，纽扣预送至送扣机与钉扣机中间待机（待机位置可设置），比常规送扣速度快；
5、独创的扣夹座带调节功能：轻松调节长柄、短柄位置，采用独特的仿钮扣轮廓设计的扣夹，夹扣更稳定。无需松开扣夹座螺丝重新安装，换扣更方便快捷。
6、震动盘自动升降功能：只需在界面按“ 震动盘升、震动盘降 ”，系统自动调节震动盘上下位置，调节方便快捷。
7、机臂纽扣扣柄长短调节：根据纽扣柄长短，通过调节螺丝根据实际要求快速调节，调节方便快捷；
8、扣夹挡扣：采用气缸挡扣模式，纽扣不跑偏，夹扣更稳固。
9、输扣槽 ：独特设计简洁高效的输扣槽采用底部、上部吹气，不卡扣送扣更顺畅 ，定时返吹装置：使纽扣不会堵在输扣槽进口处。
10、伺服电机：采用大功率伺服电机送扣，送扣速度快、震动小噪音低，送扣效率更高。
11、防碰撞功能：在操作时踩住脚踏不放连续送扣，不会出现机臂跟钉扣机扣夹相撞。

任意搭配：

该设备可搭配重机、兄弟款等各种品牌、型号的钉扣机，还可以搭配服装厂现有在使用的钉扣机上，大大节省了重新购买新钉扣机的费用。

Special features:

1. One machine dual use: Simply press the logo on/off to easily switch between logo recognition and regular button feeding modes.
2. Character recognition system: Convert the logo pattern on the button to the desired direction through the recognition system, such as: (up and down logo or left and right logo), so that the logo of the sewn clothing button faces in the same direction.
3.Adopt PLC touch screen operating system, more stable software, more intuitive page;
4.Adopt two feeding ways:normal feeding,advanced feeding,freely convert as needed.Normal feed:feeding buttons from begging to the end directly .Advanced feed:Turn on First,then set the ready position after the arm picks buttons.
5.Unique clip seat include adjustment function: adjust long-handle buttons,short-handle buttons easily. Adopt unique imitation button contour design buckle clip,buckle more stable,no need to loosen the buckle clamp screw to reinstall,buckle change more convenient and fast.
6.Vibrating disk up and down function: just press "Vibration disc up and down" on the interface, and the system will automatically adjust the up and down positions of the vibration disc, making adjustment convenient and fast.
7.Adjustment of the handle length of the arm button:according to the length of the handle it can be adjusted quickly and conveniently by adjusting screws according to the actual requirements.
8.Clamp blocker:adopt cylinder blockle mode,the button does not run off and the clop is more stable.
9.Feeding buckle track:Unique design simple and efficient track adopts bottom and upper air blowing,no stuck more smoothly feeding .Timing backblowing device:the buttons will not be blocked at the inlet of the feeding track.
10.Servo motor:Adopt big power servo motor control, high speed ,no noisy,higher efficient.
11.Anti-collision function: when operating,step on the foot pedal and do not release, the machine continuous feeding buttons, the arm of the machine will not collide with the buckle clip of the sewing head.

Variety models supporting:

This feeder can match all kinds brands of brother、JUKI type button sewing machine, also can match existing machine which the factory already using, save the cost and no need to buy one more new button sewing machine.

型号	钉扣速度（常规/识别）(pcs/min)	连续送扣速度（常规/识别）(pcs/min)	纽扣识别率	纽扣直径（常规/识别）(mm)	纽扣厚度(mm)	额定功率(W)	建议气压(Mpa)	包装尺寸(mm)	重量(kg)
Model	Button Sewing Speed(Standard / Logo)	Button Feeding Speed(Standard / Logo)	Recognation Rate	Button Diameter(Standard / Logo)	Button Thickness	Rated Power	Suggested Air Pressure	Package Size	Weight
JM-917S	40-50/35-45	60-65/32-42	95%	10-30/10-22	10	800	0.40-0.55	620x540x510	60
JM-917S-4-2	40-50/35-45	60-65/32-42	95%	10-30/10-22	10	800	0.40-0.55	1230x740x1330	140

JEMA®
箭马中国切带机领先品牌之一
JEMA is a Top Brand of Cutting Machine in China

JM-998S

LOGO识别自动送扣机

Automatic Button Feeder(LOGO)





功能特性：

1、一机双用：常规纽扣 /LOGO、图案纽扣一键互换。
2、一键测宽测厚功能：更换不同扣子时，只需按下测厚按键，测厚板自动抬起，轻松放进纽扣，输扣槽、测厚自动调节到位。
3、同时可钉大小扣功能：在服装门襟、领口、袖口钉不同大小扣子时，只需在系统里输入一件服装大扣几颗、小扣几颗，机器在钉大小扣时自动切换，一道工序一次完成，无需用户在遇到大小扣时用二道工序。
4、一键四孔、两孔纽扣转换功能。
5、支持钉扣机二次剪线功能。
6、防碰撞功能：在操作时踩住脚踏不放连续送扣，不会出现摇臂跟钉扣机扣夹相撞。
7、一键切换钉大扣功能：钉大纽扣(纽扣直径≥20mm)时，只需在屏幕上开启“ 大扣 开 ”，系统参数自动调整。

Special features:

1. Double functional: Interface of logo function, one keyboard toggle.
2.One-click width and thickness measurement function:If different size of buttons,just press one button and put one buttons into the thickness measurement plate,adjusting the width、blocker and thickness automatically.
3. Double functional:Two different size of buttons settled in one programe,size change automatically,no need manual insert ,easy operation,improvement of production efficiency.
4. Function for two-hole button.
5. Support second time thread trimming function.
6. Anti-collision system: Operator foot on the pedal long times continue feeding button, mechnical system no collisions.
7. One key to open the "big button" function: When sewing big buttons (button diameter ≥20mm), only need to open "big button ON" on the screen, and the system parameters will be adjusted automatically.

型　号	钉扣速度（常规/识别）(pcs/min)	连续送扣速度（常规/识别）(pcs/min)	送扣稳定性	纽扣识别率	纽扣直径（常规/识别）(mm)	电源电压(v)	额定功率(w)	建议气压(Mpa)	包装尺寸L.W.H(mm)	重量(kg)
Model	Button Sewing Speed(Standard / Logo)	Button Feeding Speed(Standard / Logo)	Button Feeding Stability	Recognation Rate	Button Diameter(Standard / Logo)	Voltage	Rated Power	Suggested Air Pressure	Package Size	Weight
JM-998S	40-50/35-45	60-65/32-42	99.7%	90-95%	10-28/10-22	220	80	0.3-0.35	725x575x580	55

JM-998S-1903

LOGO识别自动送扣机

Automatic Button Feeder(LOGO)





功能特性：

1、一机双用：常规纽扣 /LOGO、图案纽扣一键互换。
2、一键测宽测厚功能：更换不同扣子时，只需按下测厚按键，测厚板自动抬起，轻松放进纽扣，输扣槽、测厚自动调节到位。
3、同时可钉大小扣功能：在服装门襟、领口、袖口钉不同大小扣子时，只需在系统里输入一件服装大扣几颗、小扣几颗，机器在钉大小扣时自动切换，一道工序一次完成，无需用户在遇到大小扣时用二道工序。
4、一键四孔、两孔纽扣转换功能。
5、支持钉扣机二次剪线功能。
6、防碰撞功能：在操作时踩住脚踏不放连续送扣，不会出现摇臂跟钉扣机扣夹相撞。
7、一键切换钉大扣功能：钉大纽扣(纽扣直径≥20mm)时，只需在屏幕上开启“ 大扣 开 ”，系统参数自动调整。

Special features:

1. Double functional: Interface of logo function, one keyboard toggle.
2.One-click width and thickness measurement function:If different size of buttons,just press one button and put one buttons into the thickness measurement plate,adjusting the width、blocker and thickness automatically.
3. Double functional:Two different size of buttons settled in one programe,size change automatically,no need manual insert ,easy operation,improvement of production efficiency.
4. Function for two-hole button.
5. Support second time thread trimming function.
6. Anti-collision system: Operator foot on the pedal long times continue feeding button, mechnical system no collisions.
7. One key to open the "big button" function: When sewing big buttons (button diameter ≥20mm), only need to open "big button ON" on the screen, and the system parameters will be adjusted automatically.

型　号	钉扣速度（常规/识别）(pcs/min)	连续送扣速度（常规/识别）(pcs/min)	送扣稳定性	纽扣识别率	纽扣直径（常规/识别）(mm)	电源电压(v)	额定功率(w)	建议气压(Mpa)	包装尺寸L.W.H(mm)	重量(kg)
Model	Button Sewing Speed(Standard / Logo)	Button Feeding Speed(Standard / Logo)	Button Feeding Stability	Recognation Rate	Button Diameter(Standard / Logo)	Voltage	Rated Power	Suggested Air Pressure	Package Size	Weight
JM-998S -1903	40-50/35-45	60-65/32-42	99.7%	90-95%	10-28/10-22	220	80	0.3-0.35	1230x740x1330	185

JM-998SS

LOGO识别自动送扣机（双摄像头）

Automatic Button Feeder (Dual Camera)





功能特性：

1、一机双用：常规纽扣 /LOGO、图案纽扣一键互换。
2、正反面识别：通过视觉识别系统及吹气系统，将正面纽扣快速识别通过轨道，反面纽扣吹掉。
3、一键测宽测厚功能：更换不同扣子时，只需按下测厚按键，测厚板自动抬起，轻松放进纽扣，输扣槽、测厚自动调节到位。
4、同时可钉大小扣功能：在服装门襟、领口、袖口钉不同大小扣子时，只需在系统里输入一件服装大扣几颗、小扣几颗，机器在钉大小扣时自动切换，一道工序一次完成，无需用户在遇到大小扣时用二道工序。
5、一键四孔、两孔纽扣转换功能。
6、支持钉扣机二次剪线功能。
7、防碰撞功能：在操作时踩住脚踏不放连续送扣，不会出现摇臂跟钉扣机扣夹相撞。
8、一键切换钉大扣功能：钉大纽扣(纽扣直径≥20mm)时，只需在屏幕上开启“ 大扣 开 ”，系统参数自动调整。

Special features:

1. Double functional: Interface of logo function, one keyboard toggle.
2. Front and back recognition: By using a visual recognition system and a blowing system, the front button is quickly recognized through the track and the back button is blown off.
3.One-click width and thickness measurement function:If different size of buttons,just press one button and put one buttons into the thickness measurement plate,adjusting the width、blocker and thickness automatically.
4. Double functional:Two different size of buttons settled in one programe,size change automatically,no need manual insert ,easy operation,improvement of production efficiency.
5. Function for two-hole button.
6. Support second time thread trimming function.
7. Anti-collision system: Operator foot on the pedal long times continue feeding button, mechnical system no collisions.
8. One key to open the "big button" function: When sewing big buttons (button diameter ≥20mm), only need to open "big button ON" on the screen, and the system parameters will be adjusted automatically.

型　号	钉扣速度（常规/识别）(pcs/min)	连续送扣速度（常规/识别）(pcs/min)	送扣稳定性	纽扣识别率	纽扣直径（常规/识别）(mm)	电源电压(v)	额定功率(w)	建议气压(Mpa)	包装尺寸L.W.H(mm)	重量(kg)
Model	Button Sewing Speed(Standard / Logo)	Button Feeding Speed(Standard / Logo)	Button Feeding Stability	Recognation Rate	Button Diameter(Standard / Logo)	Voltage	Rated Power	Suggested Air Pressure	Package Size	Weight
JM-998SS	40-50/35-45	60-65/32-42	99.7%	90-95%	10-28/10-22	220	80	0.3-0.35	725x575x580	57



JM-998

自动送扣机（电机款）

Automatic Button Feeder (Motor)



功能特性：

1、电控系统：采用公司开发的 PLC 集成系统，其运行处理器速度快，故障率低，维修非常方便。
2、一键测宽测厚功能：更换不同扣子时，只需按下测厚按键，测厚板自动抬起，轻松放进纽扣，输扣槽、测厚自动调节到位。
3、电机送扣：采用高精度步进电机送扣方式，送扣位置极其精准无误，送扣速度快、送扣柔和，噪音小，使用寿命长。
4、同时可钉大小扣功能：在服装门襟、领口、袖口钉不同大小扣子时，只需在系统里输入一件服装大扣几颗、小扣几颗，机器在钉大小扣时自动切换，一道工序一次完成，无需用户在遇到大小扣时用 2 道工序。
5、一键四孔、两孔纽扣转换功能。
6、支持钉扣机二次剪线功能。
7、防碰撞功能：在操作时踩住脚踏不放连续送扣，不会出现摇臂跟钉扣机扣夹相撞。
8、一键切换钉大扣功能：钉大纽扣(纽扣直径≥20mm)时，只需在屏幕上开启“ 大扣 开 ”，系统参数自动调整。

任意搭配：

该设备可搭配重机、兄弟款等各种品牌、型号的钉扣机，还可以搭配服装厂现有在使用的钉扣机上，大大节省了重新购买新钉扣机的费用。

Special features:

1. Electric control system: Adopting the PLC integrated system developed by the company, it has fast processor speed, low failure rate, and very convenient maintenance.
2. One-click width and thickness measurement function:If different size of buttons,just press one button and put one buttons into the thickness measurement plate,adjusting the width、blocker and thickness automatically.
3. Motor button feeding: Adopting high-precision stepper motor button feeding method, the feeding position is extremely precise、accurate、fast、and soft, the noise is low, and the service life is long.
4. Double functional:Two different size of buttons settled in one programe,size change automatically,no need manual insert ,easy operation,improvement of production efficiency.
5. Function for two-hole button.
6. Support second time thread trimming function.
7. Anti-collision system: Operator foot on the pedal long times continue feeding button, mechnical system no collisions.
8. One key to open the "big button" function: When sewing big buttons (button diameter ≥20mm), only need to open "big button ON" on the screen, and the system parameters will be adjusted automatically.

型　号	额定钉扣速度 (pcs/min)	连续送扣速度 (pcs/min)	送扣稳定性	纽扣直径 (mm)	电源电压 (v)	额定功率 (w)	建议气压 (Mpa)	包装尺寸 L.W.H (mm)	重量 (kg)
Model	Rated Button Sewing Speed	Continuous Button Feeding Speed	Button Feeding Stability	Button Diameter	Voltage	Rated Power	Suggested Air Pressure	Package Size	Weight
JM-998	40-50	60-65	99.7%	9-28	220	80	0.3-0.35	620x540x510	45



JM-998-1903

自动送扣机（电机款）

Automatic Button Feeder (Motor)



功能特性：

1、电控系统：采用公司开发的 PLC 集成系统，其运行处理器速度快，故障率低，维修非常方便。
2、一键测宽测厚功能：更换不同扣子时，只需按下测厚按键，测厚板自动抬起，轻松放进纽扣，输扣槽、测厚自动调节到位。
3、电机送扣：采用高精度步进电机送扣方式，送扣位置极其精准无误，送扣速度快、送扣柔和，噪音小，使用寿命长。
4、同时可钉大小扣功能：在服装门襟、领口、袖口钉不同大小扣子时，只需在系统里输入一件服装大扣几颗、小扣几颗，机器在钉大小扣时自动切换，一道工序一次完成，无需用户在遇到大小扣时用 2 道工序。
5、一键四孔、两孔纽扣转换功能。
6、支持钉扣机二次剪线功能。
7、防碰撞功能：在操作时踩住脚踏不放连续送扣，不会出现摇臂跟钉扣机扣夹相撞。
8、一键切换钉大扣功能：钉大纽扣(纽扣直径≥20mm)时，只需在屏幕上开启“ 大扣 开 ”，系统参数自动调整。

任意搭配：

该设备可搭配重机、兄弟款等各种品牌、型号的钉扣机，还可以搭配服装厂现有在使用的钉扣机上，大大节省了重新购买新钉扣机的费用。

Special features:

1. Electric control system: Adopting the PLC integrated system developed by the company, it has fast processor speed, low failure rate, and very convenient maintenance.
2. One-click width and thickness measurement function:If different size of buttons,just press one button and put one buttons into the thickness measurement plate,adjusting the width、blocker and thickness automatically.
3. Motor button feeding: Adopting high-precision stepper motor button feeding method, the feeding position is extremely precise、accurate、fast、and soft, the noise is low, and the service life is long.
4. Double functional:Two different size of buttons settled in one programe,size change automatically,no need manual insert ,easy operation,improvement of production efficiency.
5. Function for two-hole button.
6. Support second time thread trimming function.
7. Anti-collision system: Operator foot on the pedal long times continue feeding button, mechnical system no collisions.
8. One key to open the "big button" function: When sewing big buttons (button diameter ≥20mm), only need to open "big button ON" on the screen, and the system parameters will be adjusted automatically.

型　号	额定钉扣速度 (pcs/min)	连续送扣速度 (pcs/min)	送扣稳定性	纽扣直径 (mm)	电源电压 (v)	额定功率 (w)	建议气压 (Mpa)	包装尺寸 L.W.H (mm)	重量 (kg)
Model	Rated Button Sewing Speed	Continuous Button Feeding Speed	Button Feeding Stability	Button Diameter	Voltage	Rated Power	Suggested Air Pressure	Package Size	Weight
JM-998-1903	40-50	60-65	99.7%	9-28	220	80	0.3-0.35	1230x740x1330	175



JM-988

自动送扣机（旋转气缸）

Automatic Button Feeder(Rotary Cylinder)



功能特性：

1、采用 PLC 触摸屏操作系统，软件更稳定，页面更直观。
2、一键测宽测厚功能：更换不同扣子时，只需按下测厚按键，测厚板自动抬起，轻松放进纽扣，输扣槽、测厚自动调节到位。
3、气缸送扣：采用旋转气缸送扣方式，送扣位置极其精准无误，可以做到百分之百的准确，送扣柔和，无噪音，使用寿命长。
4、支持钉扣机二次剪线功能。
5、一键切换钉大扣功能：钉大纽扣(纽扣直径≥20mm)时，只需在屏幕上开启“ 大扣 开 ”，系统参数自动调整。
6、防碰撞功能：在操作时踩住脚踏不放连续送扣，不会出现摇臂跟钉扣机扣夹相撞。

任意搭配：

该设备可搭配重机、兄弟款等各种品牌、型号的钉扣机，还可以搭配服装厂现有在使用的钉扣机上，大大节省了重新购买新钉扣机的费用。

Special features:

1.Hd touch panel , PLC system,more stable of the software,more intuitive of the page.
2. One-click width and thickness measurement function:If different size of buttons,just press one button and put one buttons into the thickness measurement plate,adjusting the width、blocker and thickness automatically.
3. We adopt rotary cylinder feeding system, feeding buttons hundred percent of accurately and correctly. Feeding way softly, no soise, long life using.
4. Support second time thread trimming function.
5. One key to open the "big button" function: When sewing big buttons (button diameter ≥20mm), only need to open "big button ON" on the screen, and the system parameters will be adjusted automatically.
6. Anti-collision system: Operator foot on the pedal long times continue feeding button, mechnical system no collisions.

型　号	额定钉扣速度 (pcs/min)	连续送扣速度 (pcs/min)	送扣稳定性	纽扣直径 (mm)	电源电压 (v)	额定功率 (w)	建议气压 (Mpa)	包装尺寸 L.W.H (mm)	重量 (kg)
Model	Rated Button Sewing Speed	Continuous Button Feeding Speed	Button Feeding Stability	Button Diameter	Voltage	Rated Power	Suggested Air Pressure	Package Size	Weight
JM-988	40-50	60-65	99.7%	9-28	220	80	0.3-0.35	620x540x510	40



JM-988-373D

自动送扣机（旋转气缸）

Automatic Button Feeder(Rotary Cylinder)



功能特性：

1、采用 PLC 触摸屏操作系统，软件更稳定，页面更直观。
2、一键测宽测厚功能：更换不同扣子时，只需按下测厚按键，测厚板自动抬起，轻松放进纽扣，输扣槽、测厚自动调节到位。
3、气缸送扣：采用旋转气缸送扣方式，送扣位置极其精准无误，可以做到百分之百的准确，送扣柔和，无噪音，使用寿命长。
4、支持钉扣机二次剪线功能。
5、一键切换钉大扣功能：钉大纽扣(纽扣直径≥20mm)时，只需在屏幕上开启“ 大扣 开 ”，系统参数自动调整。
6、防碰撞功能：在操作时踩住脚踏不放连续送扣，不会出现摇臂跟钉扣机扣夹相撞。

任意搭配：

该设备可搭配重机、兄弟款等各种品牌、型号的钉扣机，还可以搭配服装厂现有在使用的钉扣机上，大大节省了重新购买新钉扣机的费用。

Special features:

1.Hd touch panel , PLC system,more stable of the software,more intuitive of the page.
2. One-click width and thickness measurement function:If different size of buttons,just press one button and put one buttons into the thickness measurement plate,adjusting the width、blocker and thickness automatically.
3. We adopt rotary cylinder feeding system, feeding buttons hundred percent of accurately and correctly. Feeding way softly, no soise, long life using.
4. Support second time thread trimming function.
5. One key to open the "big button" function: When sewing big buttons (button diameter ≥20mm), only need to open "big button ON" on the screen, and the system parameters will be adjusted automatically.
6. Anti-collision system: Operator foot on the pedal long times continue feeding button, mechnical system no collisions.

型　号	额定钉扣速度 (pcs/min)	连续送扣速度 (pcs/min)	送扣稳定性	纽扣直径 (mm)	电源电压 (v)	额定功率 (w)	建议气压 (Mpa)	包装尺寸 L.W.H (mm)	重量 (kg)
Model	Rated Button Sewing Speed	Continuous Button Feeding Speed	Button Feeding Stability	Button Diameter	Voltage	Rated Power	Suggested Air Pressure	Package Size	Weight
JM-988-373D	40-50	60-65	99.7%	9-28	220	80	0.3-0.35	1230x740x1330	125



JM-988A

自动送扣机（笔型气缸）

Automatic Button Feeder(Pen Cylinder)



功能特性：

1、采用 PLC 触摸屏操作系统，软件更稳定，页面更直观。
2、一键测宽测厚功能：更换不同扣子时，只需按下测厚按键，测厚板自动抬起，轻松放进纽扣，输扣槽、测厚自动调节到位。
3、气缸送扣：采用笔型气缸送扣方式，送扣位置极其精准无误，可以做到百分之百的准确，送扣柔和，无噪音，使用寿命长。
4、支持钉扣机二次剪线功能。
5、一键切换钉大扣功能：钉大纽扣(纽扣直径≥20mm)时，只需在屏幕上开启“ 大扣 开 ”，系统参数自动调整。
6、防碰撞功能：在操作时踩住脚踏不放连续送扣，不会出现摇臂跟钉扣机扣夹相撞。

任意搭配：

该设备可搭配重机、兄弟款等各种品牌、型号的钉扣机，还可以搭配服装厂现有在使用的钉扣机上，大大节省了重新购买新钉扣机的费用。

Special features:

1.Hd touch panel , PLC system,more stable of the software,more intuitive of the page.
2. One-click width and thickness measurement function:If different size of buttons,just press one button and put one buttons into the thickness measurement plate,adjusting the width、blocker and thickness automatically.
3. We adopt pen cylinder feeding system, feeding buttons hundred percent of accurately and correctly. Feeding way softly, no soise, long life using.
4. Support second time thread trimming function.
5. One key to open the "big button" function: When sewing big buttons (button diameter ≥20mm), only need to open "big button ON" on the screen, and the system parameters will be adjusted automatically.
6. Anti-collision system: Operator foot on the pedal long times continue feeding button, mechnical system no collisions.
Variety models supporting
This feeder can match all kinds brands of brother 、JUKI type button sewing machine, also can match existing machine which the factory already using,save the cost and no need to buy one more new button sewing machine.

型　号	额定钉扣速度 (pcs/min)	连续送扣速度 (pcs/min)	送扣稳定性	纽扣直径 (mm)	电源电压 (v)	额定功率 (w)	建议气压 (Mpa)	包装尺寸 L.W.H (mm)	重量 (kg)
Model	Rated Button Sewing Speed	Continuous Button Feeding Speed	Button Feeding Stability	Button Diameter	Voltage	Rated Power	Suggested Air Pressure	Package Size	Weight
JM-988A	40-50	60-65	99.7%	9-28	220	80	0.3-0.35	620x540x510	40



JM-988A-373D

自动送扣机（笔型气缸）

Automatic Button Feeder(Pen Cylinder)



功能特性：

1、采用 PLC 触摸屏操作系统，软件更稳定，页面更直观。
2、一键测宽测厚功能：更换不同扣子时，只需按下测厚按键，测厚板自动抬起，轻松放进纽扣，输扣槽、测厚自动调节到位。
3、气缸送扣：采用笔型气缸送扣方式，送扣位置极其精准无误，可以做到百分之百的准确，送扣柔和，无噪音，使用寿命长。
4、支持钉扣机二次剪线功能。
5、一键切换钉大扣功能：钉大纽扣(纽扣直径≥20mm)时，只需在屏幕上开启“ 大扣 开 ”，系统参数自动调整。
6、防碰撞功能：在操作时踩住脚踏不放连续送扣，不会出现摇臂跟钉扣机扣夹相撞。

任意搭配：

该设备可搭配重机、兄弟款等各种品牌、型号的钉扣机，还可以搭配服装厂现有在使用的钉扣机上，大大节省了重新购买新钉扣机的费用。

Special features:

1.Hd touch panel , PLC system,more stable of the software,more intuitive of the page.
2. One-click width and thickness measurement function:If different size of buttons,just press one button and put one buttons into the thickness measurement plate,adjusting the width、blocker and thickness automatically.
3. We adopt pen cylinder feeding system, feeding buttons hundred percent of accurately and correctly. Feeding way softly, no soise, long life using.
4. Support second time thread trimming function.
5. One key to open the "big button" function: When sewing big buttons (button diameter ≥20mm), only need to open "big button ON" on the screen, and the system parameters will be adjusted automatically.
6. Anti-collision system: Operator foot on the pedal long times continue feeding button, mechnical system no collisions.
Variety models supporting
This feeder can match all kinds brands of brother 、JUKI type button sewing machine, also can match existing machine which the factory already using,save the cost and no need to buy one more new button sewing machine.

型　号	额定钉扣速度 (pcs/min)	连续送扣速度 (pcs/min)	送扣稳定性	纽扣直径 (mm)	电源电压 (v)	额定功率 (w)	建议气压 (Mpa)	包装尺寸 L.W.H (mm)	重量 (kg)
Model	Rated Button Sewing Speed	Continuous Button Feeding Speed	Button Feeding Stability	Button Diameter	Voltage	Rated Power	Suggested Air Pressure	Package Size	Weight
JM-988A-373D	40-50	60-65	99.7%	9-28	220	80	0.3-0.35	1230x740x1330	125


JM-373D


JM-373


JM-377/371

JM-373D/373/371/377

高速电脑直驱钉扣机

Direct Drive Button Sewing Machine







功能特性：

主要用于二孔或四孔的平纽扣缝钉，若加附具，可缝钉带柄及其他纽扣，适用于轻薄中厚面料的钉扣。

JM-371 适用于袜子、商标、纸牌等；

JM-377 适用于钉雨伞；

Special features:

This machine is applicable for button with two or four holes. Shanked button and others are also can be sewn by equipping with accessories. Tt' s suitable for light and weight material.

JM-371 button sewing machine socks, labels, cards;

JM-377 button sewing machine suitable for nail umbrella.

型 号	机针	纽扣直径 (mm)	自动剪线	压脚高度 (mm)	钉缝针数		转速 (r/min)	电压 (mv)	体积 (v)	重量 (kg)
Model	Needle	Button Diameter	Auto Matic Trim	Height of Presser Foot	Stich No.		Speed	Voltage	Packing Size	Weight
JM-373D	14#~18# TQX1 #16	10~28	X(2.5~6.5) Y(0,2.5~6.5)	>9	8,16,32	L M	0-1500	110/220	580x440x430	27/29
JM-373	14#~18# TQX1 #16	10~28	X(2.5~6.5) Y(0,2.5~6.5)	>9	8,16,32,6,12,24	L M	0-1500	220/380	505x330x430	24/27
JM-371	14#~18# TQX1 #16	10~28	X(2.5~6.5) Y(0,2.5~6.5)	>9	4,8,16,6,12,24	L M	0-1500	110/220	505x330x430	27/27
JM-377	TQX7 175X7 14/90	-	X(2.5~6.5) Y(0,2.5~6.5)	>9	13,15	L M	0-1500	220/380	505x330x430	24/27


JM-2377D


JM-2373

JM-2377D/2373

高速电脑直驱钉扣机

Direct Drive Button Sewing Machine







功能特性：

快速适应多种缝制要求，对应缝制的变化，可通过简单的操作进行从 4 孔到 2 孔钉扣形式的变更。也可以通过简单操纵杆转换 "=" 与 "X"。

Special features:

This machine is able to over the stitching mode between 2 holed and 4 holed buttons according to any design change. In addition, stitch shape can be easily changed over between "=" and "X".

型 号	机针	纽扣直径 (mm)	自动剪线	压脚高度 (mm)	钉缝针数		转速 (r/min)	电压 (v)	体积 (mm)	重量 (kg)
Model	Needle	Button Diameter	Auto Matic Trim	Height of Presser Foot	Stich No.		Speed	Voltage	Packing Size	Weight
JM-2377D	14#~18# TQX1 #16	10~28	X(2.5~6.5) Y(0,2.5~6.5)	>9	8,16,32,6,12,24	L M	0-1500	110/220	580x465x430	27/32
JM-2373	14#~18# TQX1 #16	10~28	X(2.5~6.5) Y(0,2.5~6.5)	>9	8,16,32,6,12,24	L M	0-1500	220/380	505x330x430	24/29



JM-B11

省布机（固定/活络长手柄）

End Cutter (Fixed Handed / Free Handle)



功能特性：

本机是服装、针织行业生产裁断必备工具。适用于批量生产时，规格尺寸之裁断。具备快速刃磨装置，能确保刀口锋利。能平整压布，可齐整不错位裁断。能显示自动计数。

Special features:

It is needs for cutting the fabric in large batches, such as cotton, wool, linen etc. Carry with a grinder, it can easily sharpen. It can mack the fabric level, and neatly cutted. It can auto show the counter.

型 号	功率 (w)	电 压 (V)	频 率 (Hz)	裁剪宽度 (m)	导轨长度 (m)	刀片转速 (r/min)	重 量 (kg)	包装尺寸 (L.W.H)mm	装箱率 (台)
Model	Rating Power	Rating Voltage	Frequency	Cutting Width	Guide Length	Inserts Degree Turn	Weight	Package Size	Loading Rate
JM-B11	120	220	50/60	1.5 1.7 1.9 2.1 2.3 2.5	2.0 2.2 2.4 2.5 2.6 2.8 3.0 3.2	15000	14	760×445×190	机器1 导轨 1



JM-801/802A

切布条机

Cloth Strip Cutter

功能特性

本机是专门为针织捆条切裁而造。机械性能卓越，捆条宽度可以调节，最大可达 100 毫米，特别设计的送布轮使操作更简便。性能卓越，操作简便。

Special features:

This strongly construched machine is fully used in the manufacture of knitting tapes. Grade of work is accomplish on this machine, which is the perfect tool for this work. The width of bundle tapes is adjustable up to 100mm. The cloth feed will be very smooth at your working.

with the design of single & double blade, it is hig.JMy effective and easy to use.

型 号	速度 (m/h)	皮带轮	转速 (r/min)	电压 (v)	频率 (Hz)	功率 (kw)	包装尺寸 L.W.H (mm)	重 量 (kg)	装箱率 (台)
	Capacity	Motor Pully	Speed	Voltage	Frequency	Power	Package Size	Weight	Loading Rate Pic
JM-801A	3000	4"~5.5"	1400	220	50/60	1/4	820x350x240	25	1
JM-802A	3000	4"~5.5"	1400	220	50/60	1/4	820x350x240	25	1


JM-3D　JM-3　JM-103　JM-108

JM-3D/3/103/108

电动裁剪机

Computerized Straight Knife Cutting Machine

功能特性

JM-3D/3/103 电动裁剪机可与 KMCK8-EU 型伊士曼电剪 627X 型互通用，适用于棉、毛、麻、丝绸、化纤、皮革等厚料裁剪。本机具有集中润滑，切口平直，且能作小曲率半径曲线裁剪，低噪音，运转平稳，操作简便，高效率，自动磨刀，采用大功率电动机等特点，是服装行业最理想的裁剪工具。

JM-108 自动磨刀裁剪机可与 KM (KS-EU) 型互换，适用于棉、毛、麻、丝绸、化纤、皮革织物裁剪。有单相或三相电源可选。

本机规格齐全，功率大，并装有自动磨刀装置和自动润滑系统。具有工作平稳，操作灵便和剪裁能力强等特点，是服装行业最理想的裁剪工具。

Special features:

JM-3D/3/103 it can be exchanged with Eastman 627xModel. It is available to cutting atsrials such as cotton, woolens, linen, silk, chemical fiber and leather etc.Having featuresof concentrated lubrication, neat cutting section and small curviliear cutting, low noise, stable running, easy operation, and high efficency, automatic knife grinding, Powerful motor, this machine is and ideal cutting tool for garment industry.

JM-108 auto-sharpening cutting machine can be exchanged with KM (KS-EU) Model. It is available to cutting materials such as cotton, woolens, linen, silk, chemical fiber, leathers etc. It is single / three/phase.

Having features of lower noise, automatic sharpening, flexible and steady operation, it is a necessary equipment of garment industry.

型 号	裁剪高度 (mm)	电机转速 (r/min)	电压 (v)	频率 (Hz)	功率 (w)	包装尺寸 L.W.H (mm)	重 量 (kg)	装箱率 (台)
Model	Cutting Height	Motor Speed	Voltage	Frequency	Power	Package Size	Weight	Loading Rate Pic
JM-3D	210 160	3000	110/220	50/60	550/1400	760x405x320	15	1
JM-3	260 210 160	2800/3450	110/220	50/60	550/750	760x400x325	19 18 17	1
JM-103	260 210 160	2800/3450	110/220	50/60	550/750	660x360x265	19 18 17	1
JM-108	90	2800/3400	110/220/380	50/60	370	530x320x232	9	1


加热



JM-1-1/1-2

高速布料钻孔机（电加热）

High-speed Cloth Drilling Machine (Electric Heating)



功能特性

本机是服装生产中不可缺少的专用设备之一，适用于棉、毛、麻、丝绸、化纤等布料钻印记孔的工作。

本机体积小、重量轻，操作方便。钻印用的钢针有粗、细两种规格，钻印时操作者可根据布料特点进行选用。本机电源为单相，电压为 220 伏，适宜不具备三相电源的用户使用。

Special features:

This machine is one of necessary equipment used in clothing production. It is suitable for drill printing mark holes onto the cotton, wool, linen, silk and chemical fabric materials.

It has the ment of compact size, light weight and convenient operation. The steel Needle have two standards which of thicker and thinner so as to let operator choose for it according to various clothing materals. The power source of single phase, voltage 220V is more available for those users who hasn't 3-phase power.

型 号	包装尺寸 L.W.H (mm)	重 量 (kg)	装箱率 (台)
Model	Package Size	Weight	Loading Rate Pic
JM-1-1	575x295x255	6	1
JM-1-2(加热)	575x295x255	6	1

了解切带机的三步曲
LEARN TRILOGY CUTTING MACHINE

切带机是什么机器？ Cutting machine, what's this machine?

切带机是集气、机电一体化的新型专机，它是用输入电脑程序自动控制机械、气缸的动作，利用刀片或声波来切断材料，是一款切断各种带状物品的专用设备。目前有机械式切带机、电脑切带机、超声波电脑切带机等。

Cutting machine is a air cylinder、mechanotronics mechanical-electrical integration new special machines, which is entered into a computer program to automatically control machinery、cylinder movement, through to using the blade or ultrasonic waves to cut off all kinds of ribbon items of special equipment. There are have mechanical cutting machine, automatic cutting machine, ultrasonic automatic cutting machine etc.

切带机是用在哪些领域？ Cutting machine, what fields is this machine used for?

该设备是用在：箱包的包带切断、鞋、帽上的带子、魔术贴、各种商标、塑料软管、各种拉链、各种软电线、电脑排线、胀缩管、松紧带等。

Cutting machine is used for: bag band cutting, shoes, hats tape, velcro, elastic bands, Soft plast tube, computer cables, all kinds of labels, zippers and fine wire.

切带机能给用户带来什么好处？ What advantage does this cutting machine give to users?

该设备能使用户提高产品质量、提高产品效益、据用户反馈：（使用该设备一台机器可以节省 2–3 个工人）。

Cutting machine enable users to promote products quality, improve produce efficiency, according to user feedback: (it can save 2-3workers when we use this equipment)

产品型号认知：
Model Differentiation:

JM-120HLR

品牌名称 Brand | 系列编码 Products Series | 功能编码 Products Functions

系列编码 Products Series	切带机类别 Type of Cutting Machine
2200	超声波电脑切带机 Ultrasonic Cutting Machine
150	多功能电脑切带机 Automatic Multi-function Cutting Machine
130	电脑切带机 Heavy-duty Auto-cutting Machine
120	电脑切带机 Automatic Cutting Machine
110	简易电脑切带机 Economical Auto-cutting Machine
817	机械式切带机 Mechanical Cutting Machine

功能编码 Products Functions	功能区分 Functional Explanation
L	冷刀 Cold Knife Cutter
LR	冷、热刀 Cold & Hot Knife Cutter
H	热刀 Hot Knife Cutter
SH	热刀红外 Auto-label Hot Knife Cutter
HLR	冷、热刀红外 Auto-label Cold & Hot Knife Cutter
HL	冷刀红外 Auto-label Cold Knife Cutter
HX	热刀斜角、直角 Bevel & Straight Cutter
R	专门切魔术贴 Velcro Tape Round Shape Cutter



LR
在不加热的情况下是冷刀，可以切 L 上的所有材料。加热后可以切尼龙材质，切边热封不散丝。但对厚料、棉质材质效果不佳。

If closing the heating switch, the machine will become a cold cutter and it can cut a variety materials same as "L" . It can cut nylon materials with sealing the edge once open the heat switch except the thick and cotton materials.

L
可以切不同材质如：尼龙、棉、塑料软管、电脑排线、胀缩管等材料，但对尼龙材质切口会散丝。

It can cut a variety of different materials such as: nylon tape, cotton tape, soft plastic tube, computer cables etc, but only cold cutting without heat-sealing function.

H
可以切尼龙、松紧带、魔术贴等尼龙材质，对一般厚度材质可以热封，切边不散丝。但不能切棉质材料。

It can cutting variety of different materials same as "L" . In addition to these,especially to sealing function is good at melting normally thick materials except cotton materials.

SH
在 H 所有的功能上，通过加装红外传感器，可以切各种商标。

This same as "H" function,it has color sensor device so it also can cutting varity of different label materials.

HLR
在 LR 的所有功能上，通过加装红外传感器，可以切各种商标。

This same as "LR" function,it has color sensor device so it also can cutting varity of different label materials.

HL
在 L 的所有功能上，通过加装红外传感器，可以切各种商标。

This same as "L" function,it has color sensor device so it also can cutting varity of different label materials.

HX
斜角切出的产品是斜面的，直角切出来的产品直面的，通过刀架平台上的螺丝可以转换斜角或直角。

It is a bevel & straight cutting machine with hot knife to sealing the edge,do not change the knife and direct loosen the screw to change the knife angle to reached customers request.

R
通过客人要求宽度和形状定做刀模。

It is a velcro cutting machine,it can cutting many different shapes to reached customers request!

JEMA®
箭马中国切带机领先品牌之一
JEMA is a Top Brand of Cutting Machine in China