

Three Phase Hybrid Inverter

SUN-5/6/8/10/12K-SG04LP3-EU



Safe

- 48V low voltage battery, transformer isolation design



Intelligent

- 6 time periods for battery charging/discharging



Flexible

- AC couple to retrofit existing solar system
- Max. 10 pcs parallel for on-grid and off-grid operation; support multiple batteries parallel



Reliable

- Max. charging/discharging current of 240A
- Support storing energy from diesel generator
- 100% unbalanced output, max. output up to 50% rated power for each phase

| Model | SUN-5K -SG04LP3-EU | SUN-6K -SG04LP3-EU | SUN-8K -SG04LP3-EU | SUN-10K -SG04LP3-EU | SUN-12K -SG04LP3-EU |
|--|--|-----------------------|-----------------------|------------------------|------------------------|
| Battery Input Data | | | | | |
| Battery Type | Lead-acid or Lithium-ion | | | | |
| Battery Voltage Range (V) | 40-60 | | | | |
| Max. Charging/Discharging Current (A) | 120 | 150 | 190 | 210 | 240 |
| Charging Strategy for Li-ion Battery | Self-adaption to BMS | | | | |
| Number of Battery Input | 1 | | | | |
| PV String Input Data | | | | | |
| Max. PV access power (W) | 10000 | 12000 | 16000 | 20000 | 24000 |
| Max. PV Input Power (W) | 7500 | 9000 | 12000 | 15000 | 18000 |
| Max. PV Input Voltage (V) | 800 | | | | |
| Start-up Voltage (V) | 160 | | | | |
| MPPT Voltage Range (V) | 200-650 | | | | |
| Rated PV Input Voltage (V) | 550 | | | | |
| Max. Operating PV Input Current (A) | 13+13 | | | 26+13 | |
| Max. Input Short-Circuit Current (A) | 17+17 | | | 34+17 | |
| No. of MPP Trackers/ No. of Strings MPP Tracker | 2/1+1 | | | 2/2+1 | |
| AC Input/Output Data | | | | | |
| Rated AC Input/Output Active Power (W) | 5000 | 6000 | 8000 | 10000 | 12000 |
| Max. AC Input/Output Apparent Power (VA) | 5500 | 6600 | 8800 | 11000 | 13200 |
| Rated AC Input/Output Current (A) | 7.6/7.2 | 9.1/8.7 | 12.1/11.6 | 15.2/14.5 | 18.2/17.4 |
| Max. AC Input/Output Current (A) | 8.4/8 | 10/9.6 | 13.4/12.8 | 16.7/15.9 | 20/19.1 |
| Max. Continuous AC Passthrough (grid to load) (A) | 40 | | | | |
| Peak Power (off-grid) (W) | 2 times of rated power, 10s | | | | |
| Power Factor Adjustment Range | 0.8 leading to 0.8 lagging | | | | |
| Rated input/output voltage | 220/380V, 230/400V 0.85Un-1.1Un 3L+N+PE | | | | |
| Rated Input/Output Grid Frequency/Range(Hz) | 50/45-55, 60/55-65 | | | | |
| Total Current Harmonic Distortion THDi | <3% (of nominal power) | | | | |
| DC Injection Current | <0.5% In | | | | |
| Efficiency | | | | | |
| Max. Efficiency | 97.6% | | | | |
| Euro Efficiency | 97.0% | | | | |
| MPPT Efficiency | >99% | | | | |
| Equipment Protection | | | | | |
| Integrated | DC Reverse Polarity Protection, AC Output Overcurrent Protection, Thermal Protection, AC Output Overvoltage Protection, AC Output Short Circuit Protection, DC Component Monitoring, Arc Fault Circuit Interrupter (AFCI) (optional), Anti-islanding Protection, DC Switch, Insulation Impedance Detection, Residual Current Detection | | | | |
| Surge Protection Level | TYPE II(DC), TYPE II(AC) | | | | |
| Interface | | | | | |
| LCD/LED Display | LCD | | | | |
| Communication Interface | WIFI, RS485, CAN | | | | |
| General Data | | | | | |
| Operating Temperature Range (°C) | -40 to +60°C, >45°C Derating | | | | |
| Permissible Ambient Humidity | 0-100% | | | | |
| Permissible Altitude | 2000m | | | | |
| Noise (dB) | <55 | | | | |
| Ingress Protection(IP) Rating | IP 65 | | | | |
| Inverter Topology | Non-Isolated (solar), Isolated (battery) | | | | |
| Over Voltage Category | OVC II(DC), OVC III(AC) | | | | |
| Cabinet Size (WxHxD mm) | 422×658×254 (Excluding Connectors and Brackets) | | | | |
| Weight (kg) | 38 | | | | |
| Type of Cooling | Intelligent Air Cooling | | | | |
| Warranty | 5 Years/10 Years the Warranty Period Depends the Final Installation Site of Inverter, More Info Please Refer to Warranty Policy | | | | |
| Grid Regulation | IEC 61727, IEC 62116, CEI 0-21, EN 50549, NRS 097, RD 140, UNE 217002, OVE-Richtlinie R25, G99, VDE-AR-N 4105 | | | | |
| Safety / EMC Standard | IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2 | | | | |