

# Single Phase String Inverter

SUN-9/10/10.5K-G02P1-EU-CM2



## Efficient

- 2 MPP trackers, Max. efficiency up to 97.7%



## Intelligent

- String intelligent monitoring (optional)



## Adaptive

- Zero export application, VSG application
  - Wide output voltage range



## Reliable

- Anti-PID function (Optional)
- Low start-up voltage of 80V

Model	SUN-9K-G02P1-EU-CM2	SUN-10K-G02P1-EU-CM2	SUN-10.5K-G02P1-EU-CM2
<b>PV String Input Data</b>			
Max. PV Input Power (kW)	13.5	15	15.8
Max. PV Input Voltage (V)		550	
Start-up Voltage (V)		80	
MPPT Voltage Range (V)		70-500	
Rated PV Input Voltage (V)		360	
Max. Operating PV Input Current (A)		26+26	
Max. Input Short Circuit Current (A)		39+39	
No. of MPP Trackers/ No. of Strings MPP Tracker		2/2+2	
<b>AC Output Side</b>			
Rated AC Output Active Power (kW)	9	10	10.5
Max. AC Output Apparent Power (kVA)	9.9	11	11.55
Rated AC Output Current (A)	41/39.2	45.5/43.5	47.8/45.7
Max. AC Output Current (A)	45/43.1	50/47.9	52.5/50.3
Rated output voltage	220/230 0.85Un-1.1Un L/N/PE		
Rated Output Grid Frequency/Range(Hz)	50/45-55, 60/55-65		
Power Factor Adjustment Range	0.8 leading to 0.8 lagging		
Total Current Harmonic Distortion THDi	<3%		
DC Injection Current	<0.5In		
<b>Efficiency</b>			
Max. Efficiency	97.7%		
Euro Efficiency	97.2%		
MPPT Efficiency	>99%		
<b>Equipment Protection</b>			
DC Reverse Polarity Protection	Yes		
AC Output Overcurrent Protection	Yes		
AC Output Overvoltage Protection	Yes		
AC Output Short Circuit Protection	Yes		
Thermal Protection	Yes		
Insulation Impedance Detection	Yes		
DC Component Monitoring	Yes		
Arc Fault Circuit Interrupter (AFCI)	Optional		
Anti-islanding Protection	Yes		
Residual Current Detection	Yes		
DC Switch	Yes		
Surge Protection Level	TYPE II(DC), TYPE II(AC)		
<b>Interface</b>			
LCD/LED Display	LCD1602		
Communication Interface	RS485/RS232 /WiFi/LAN		
<b>General Data</b>			
Operating Temperature Range (°C)	-25 to +60°C, >45°C Derating		
Permissible Ambient Humidity	0-100%		
Permissible Altitude	3000m		
Noise (dB)	≤35		
Ingress Protection(IP) Rating	IP 65		
Inverter Topology	Non-Isolated		
Over Voltage Category	OVC II(DC), OVC III(AC)		
Cabinet Size (WxHxD mm)	330×410×213.5 (Excluding Connectors and Brackets)		
Weight (kg)	14.8		
Warranty	5 Years		
Type of Cooling	Natural Cooling		
Grid Regulation	IEC 61727, IEC 62116, EN 50549, NRS 097, RD 140, UNE 217002, G99		
Safety EMC/Standard	IEC/EN 61000-6-1/2/3/4, IEC/EN 62109-1, IEC/EN 62109-2		