

拉丝布 普通版 High Stich Fabric

Technical Date Sheet

Properties	Units	Test Method	Average Value
Base Fabric Yarn	D (Denier)		500*500D
Base Fabric Density	线/英寸 (Thread/Inch)	FZ/T01003	16*22
Finished Fabric Weight	克/平方米 (Gram/m ²)	FZ/T01003	2600g
Thickness	毫米 (mm)	FZ/T01003	/
Tensile Strength at MD	N/5cm	GB/T1040	/
Tensile Strength at CD	N/5cm	GB/T1040	/
Tearing Strength at MD	N/5cm	GB/T16578	/
Tearing Strength at CD	N/5cm	GB/T16578	/
Peeling Strength	N/5cm	GB/T3917	110
Temperature Range	℃		-50 ~ +70
Anti-fungal			Optional
Anti-UV			Optional
Frame Retardant			Optional

拉丝布 加强版 High Stich Fabric

Technical Date Sheet

Properties	Units	Test Method	Average Value
Base Fabric Yarn	D (Denier)		500*500D
Base Fabric Density	线/英寸 (Thread/Inch)	FZ/T01003	26*26
Finished Fabric Weight	克/平方米 (Gram/m ²)	FZ/T01003	3200/3800g
Thickness	毫米 (mm)	FZ/T01003	/
Tensile Strength at MD	N/5cm	GB/T1040	/
Tensile Strength at CD	N/5cm	GB/T1040	/
Tearing Strength at MD	N/5cm	GB/T16578	/
Tearing Strength at CD	N/5cm	GB/T16578	/
Peeling Strength	N/5cm	GB/T3917	120
Temperature Range	℃		-50 ~ +70
Anti-fungal			Optional
Anti-UV			Optional
Frame Retardant			Optional

拉丝布 加强版 High Stich Fabric

Technical Date Sheet

Properties	Units	Test Method	Average Value
Base Fabric Yarn	D (Denier)		1000*1000D
Base Fabric Density	线/英寸 (Thread/Inch)	FZ/T01003	23*23
Finished Fabric Weight	克/平方米 (Gram/m ²)	FZ/T01003	3200/3800g
Thickness	毫米 (mm)	FZ/T01003	/
Tensile Strength at MD	N/5cm	GB/T1040	/
Tensile Strength at CD	N/5cm	GB/T1040	/
Tearing Strength at MD	N/5cm	GB/T16578	/
Tearing Strength at CD	N/5cm	GB/T16578	/
Peeling Strength	N/5cm	GB/T3917	120
Temperature Range	℃		-50 ~ +70
Anti-fungal			Optional
Anti-UV			Optional
Frame Retardant			Optional