

PVC 气密船布

Technical Data Sheet

Properties	Units	Test Method	Average Value
Base Fabric Yarn	D (Denier)		1000x1000D
Base Fabric Density	线/英寸 (Thread/Inch)	FZ/T01003	28x26
Finished Fabric Weight	克/平方米 (Gram/m ²)	FZ/T01003	/
Thickness	毫米 (mm)	FZ/T01003	0.9mm ± 3%
Tensile Strength at MD	N/5cm	GB/T1040	3600
Tensile Strength at CD	N/5cm	GB/T1040	3400
Tearing Strength at MD	N/5cm	GB/T16578	340
Tearing Strength at CD	N/5cm	GB/T16578	300
Peeling Strength	N/5cm	GB/T3917	130
Temperature Range	℃		-50 ~ +70
Anti-fungal			Optional
Anti-UV			Optional
Frame Retardant			Optional

Technical Data Sheet

Properties	Units	Test Method	Average Value
Base Fabric Yarn	D (Denier)		1000x1000D
Base Fabric Density	线/英寸 (Thread/Inch)	FZ/T01003	30x30
Finished Fabric Weight	克/平方米 (Gram/m ²)	FZ/T01003	
Thickness	毫米 (mm)	FZ/T01003	1.2mm ± 3%
Tensile Strength at MD	N/5cm	GB/T1040	4300
Tensile Strength at CD	N/5cm	GB/T1040	3650
Tearing Strength at MD	N/5cm	GB/T16578	650
Tearing Strength at CD	N/5cm	GB/T16578	450
Peeling Strength	N/5cm	GB/T3917	130
Temperature Range	℃		-50 ~ +70
Anti-fungal			Optional
Anti-UV			Optional
Frame Retardant			Optional