

# 箱包布 PVC Waterproof Bag Fabric

## Technical Date Sheet

Properties	Units	Test Method	Average Value
Base Fabric Yarn	D (Denier)		500x500D
Base Fabric Density	线/英寸 (Thread/Inch)	FZ/T01003	18x17
Finished Fabric Weight	克/平方米 (Gram/m <sup>2</sup> )	FZ/T01003	610g ± 3%
Thickness	毫米 (mm)	FZ/T01003	
Tensile Strength at MD	N/5cm	GB/T1040	
Tensile Strength at CD	N/5cm	GB/T1040	
Tearing Strength at MD	N/5cm	GB/T16578	
Tearing Strength at CD	N/5cm	GB/T16578	
Peeling Strength	N/5cm	GB/T3917	
Temperature Range	℃		-50 ~ +70
Anti-fungal			Optional
Anti-UV			Optional
Frame Retardant			Optional

## Technical Date Sheet

Properties	Units	Test Method	Average Value
Base Fabric Yarn	D (Denier)		250x250D
Base Fabric Density	线/英寸 (Thread/Inch)	FZ/T01003	19x21
Finished Fabric Weight	克/平方米 (Gram/m <sup>2</sup> )	FZ/T01003	500g ± 3%
Thickness	毫米 (mm)	FZ/T01003	/
Tensile Strength at MD	N/5cm	GB/T1040	700
Tensile Strength at CD	N/5cm	GB/T1040	600
Tearing Strength at MD	N/5cm	GB/T16578	100
Tearing Strength at CD	N/5cm	GB/T16578	80
Peeling Strength	N/5cm	GB/T3917	?
Temperature Range	℃		-50 ~ +70
Anti-fungal			Optional
Anti-UV			Optional
Frame Retardant			Optional