

---

# WL2852K

## High Input Voltage, Low Quiescent Current LDO

[Http://www.sh-willsemi.com](http://www.sh-willsemi.com)

### Descriptions

The WL2852K series is a high accuracy, high input voltage low quiescent current, high speed, and low dropout Liner regulator with high ripple rejection. The device is manufactured with Bi-CMOS process.

The WL2852K offers over-current limit and over temperature protection to ensure the device working in well conditions.


The WL2852K regulators are available in standard SOT-89-3L packages. Standard products are Pb-free and Halogen-free.

### Features


- Supply Voltage : 4.75V~40V
- Output Range : 1.8V~5.7V
- Output Accuracy : <+/-2%
- Output Current : 100mA (Up to 150mA Typ.)
- PSRR : 60dB @ 100Hz
- Dropout Voltage : 800mV @  $I_{OUT}=100mA$
- Quiescent Current : 10 $\mu A$ @ $V_{IN}=7V$ (Typ.)
- Recommend Capacitor : 10uF



**SOT-89**



**Pin Configuration (Top View)**



For detail marking information, please see page 9.

**Marking**


### Order Information

For detail order information, please see page 9.

---

---


## Typical Application



## Pin Description

PIN	Symbol	Description
1	VOUT	Voltage Output
2	GND	Ground
3	VIN	Voltage Input

## Block Diagram



## Absolute Maximum Ratings

Parameter	Value	Unit
Power Dissipation	Internal limited	mW
V <sub>IN</sub> Range	-0.3~45	V
V <sub>OUT</sub> Range	-0.3~6.5	V
Lead Temperature Range	260	°C
Storage Temperature Range	-55 ~ 150	°C
Operating Junction Temperature Range	150	°C
ESD MM	400	V
ESD HBM	4K	V

## Recommend Operating Ratings


Parameter	Value	Unit
Operating Supply voltage	4.75~40	V
Operating Temperature Range	-40~85	°C
Thermal Resistance (On PCB) , R <sub>θJA</sub>	43.5	°C/W
Power Dissipation	1000	mW

## Electronics Characteristics (Ta=25°C, V<sub>IN</sub>=12V, C<sub>IN</sub>=C<sub>OUT</sub>=10uF, unless otherwise noted)


Symbol	Parameter	Test Condition	WL2852K SPEC			Unit
			Min.	Typ.	Max.	
V <sub>IN</sub>	Input Range	I <sub>OUT</sub> =10mA	4.75		40	V
V <sub>OUT</sub>	Output Range	I <sub>OUT</sub> =10mA	V <sub>OUT</sub> *0.98	V <sub>OUT</sub>	V <sub>OUT</sub> *1.02	V
ΔV <sub>OUT</sub>	Output Voltage	V <sub>IN</sub> =12V, I <sub>OUT</sub> =10mA	5.586	5.7	5.814	V
			5.194	5.3	5.406	V
			4.9	5.0	5.1	V
			3.234	3.3	3.366	V
I <sub>OUT_PK</sub>	Maximum Output Current	V <sub>IN</sub> =12V, R <sub>L</sub> =1Ω	180	280	460	mA
I <sub>Q</sub>	Quiescent Current	V <sub>IN</sub> =7V, No load		10	15	μA
		V <sub>IN</sub> =24V, No load		11	16	
		V <sub>IN</sub> =40V, No load		13	20	
V <sub>DROP</sub>	Dropout Voltage	I <sub>OUT</sub> =1mA		8	12	mV
		I <sub>OUT</sub> =100mA		800	1200	
Δ V <sub>Line</sub>	Line Regulation	V <sub>IN</sub> =7--24V, V <sub>OUT</sub> =5V I <sub>OUT</sub> =1mA		0.02		%V
		V <sub>IN</sub> =7--45V, V <sub>OUT</sub> =5V I <sub>OUT</sub> =1mA		0.1		
Δ V <sub>Load</sub>	Load Regulation	V <sub>IN</sub> =12V, I <sub>OUT</sub> =1--100mA		0.6		%
e <sub>NO</sub>	Output Noise	I <sub>OUT</sub> =10mA	-100		+100	μV
PSRR	Ripple Rejection	V <sub>IN</sub> =10V f=100Hz		60		dB
		V <sub>PP</sub> =0.5V f=1KHz		45		
		I <sub>OUT</sub> =1mA f=10KHz		35		
T <sub>SD</sub>	Thermal Protection	V <sub>IN</sub> =12V, I <sub>OUT</sub> =1mA		165		°C
T <sub>SD_HYS</sub>	Thermal Protection Hys	V <sub>IN</sub> =12V, I <sub>OUT</sub> =1mA		30		°C
ΔVo/ΔT	Temperature Coefficient	V <sub>IN</sub> =12V, I <sub>OUT</sub> =1mA		±0.5		mv/°C

---


**Typical characteristics (Ta=25°C, CIN=COUT=10µF, unless otherwise noted)**




**Quiescent Current vs. Input Voltage**




**Quiescent Current vs. Input Voltage**




**Output Voltage vs. Temperature**



**Output Voltage vs. Temperature**




**Output Voltage vs. Input Voltage**




**Output Voltage vs. Input Voltage**


---




Output Voltage vs. Load Current




Output Voltage vs. Load Current




Output Voltage vs. Load Current




Output Voltage vs. Load Current




Output Voltage vs. Load Current




Output Voltage vs. Load Current




**Dropout Voltage vs. Output Current**




**Dropout Voltage vs. Output Current**




**PSRR vs. Frequency**




**PSRR vs. Frequency**




**PSRR vs. Frequency**




**PSRR vs. Frequency**



**PSRR vs. Frequency**




**PSRR vs. Frequency**




**Quiescent Current vs. Output Current**


---




Startup from Power ON



Startup from Power ON



Shutdown from Power OFF



Shutdown from Power OFF



---

## ORDER INFORMATION

Ordering No.	Vout (V)	Package	Operating Temperature	Marking	Shipping
WL2852K33-3/TR	3.3	SOT-89	-40~+85°C	2852KDD YYWW	Tape and Reel, 1000
WL2852K50-3/TR	5.0	SOT-89	-40~+85°C	2852KFA YYWW	Tape and Reel, 1000
WL2852K53-3/TR	5.3	SOT-89	-40~+85°C	2852KFD YYWW	Tape and Reel, 1000
WL2852K57-3/TR	5.7	SOT-89	-40~+85°C	2852KFH YYWW	Tape and Reel, 1000

### Marking:

2852K\*\* = Device Code


YY = Year

WW = Week

---

## Package outline dimensions

### SOT-89-3L



Symbol	Dimensions in millimeter		
	Min.	Typ.	Max.
A	1.400	1.500	1.600
b	0.320	0.420	0.520
b1	0.400	0.490	0.580
c	0.350	-	0.440
D	4.400	4.500	4.600
D1	1.550 Ref.		
E	2.300	2.450	2.600
E1	3.940	4.100	4.250
e	1.500 Typ.		
e1	3.000 Typ.		
L	0.900	-	1.200

---